

# Product datasheet

Specifications



## Kaedra - for modular device - 3 x 12 modules - 2 terminal blocks

13435

### Main

Range	Mureva
Product name	Mureva Enclosure
Product or component type	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Mounting plate description	Without mounting plate

### Complementary

enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	36
Number of horizontal rows	3
Electrical insulation class	Double insulation Class II
Provided equipment	3 marking kit 3 wiring strap 1 terminal block support 2 terminal block 32 holes
Type of front cover	Transparent Reversible
[In] rated current	125 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	2 earth / neutral (screw connection) with 32 outgoers
Distribution block outgoers	32 x 10 mm² 32 x 16 mm²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	340 mm
Height	610 mm
Depth	160 mm
Internal depth	88 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Standards	IEC 60670 IEC 60695-2-1 IEC 61439-3 EN 50262
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.200 cm
Package 1 Width	36.000 cm
Package 1 Length	62.500 cm
Package 1 Weight	4.550 kg
Unit Type of Package 2	P12
Number of Units in Package 2	22
Package 2 Height	116.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	109.000 kg

## Contractual warranty

Warranty	18 months
----------	-----------

Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Lower Impact Materials   Transparency   RoHS/REACH

Resource performance

✓

Minimum Percentage Of Recycled Plastic Content

27

Well-being performance

✓

Rohs Exemption Information

Yes

✓

Halogen Free Product

Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations