Product datasheet

Specification





mini Kaedra - for modular device -1 openings - 4 modules - 2 terminal blocks

13441

Main

| Range | Mureva |
|----------------------------|-----------------------------------|
| Product name | Mureva Enclosure |
| Product or component type | Weatherproof enclosure |
| Enclosure type | Mini enclosure for modular device |
| Mounting plate description | Without mounting plate |

Complementary

| enclosure mounting | Surface |
|---------------------------------|--|
| 9 mm pitches | 8 |
| Number of 18 mm modules per row | 4 |
| Total number of 18 mm modules | 4 |
| Number of horizontal rows | 1 |
| Electrical insulation class | Double insulation Class II |
| Provided equipment | 1 marking kit 2 terminal block 4 holes |
| Type of front cover | Transparent |
| Power dissipation in W | 10 W |
| [In] rated current | 63 A |
| Type of rail | DIN |
| Number of pre-cutouts PG ISO | 3 |
| Number of terminal blocks | 2 earth / neutral (screw connection) with 4 outgoers |
| Distribution block outgoers | 4 x 10 mm ² 4 x 16 mm ² |
| Locking options description | Optional keylock |
| Enclosure material | Self-extinguishing polymer |
| Width | 123 mm |
| Height | 200 mm |
| Depth | 112 mm |
| Internal depth | 56 mm |
| Colour | Door: transparent green Enclosure: light grey (RAL 7035) |

Environment

| Standards | EN 50262 IEC 60695-2-1 IEC 60670 IEC 61439-3 | |
|---------------------------------------|--|--|
| Fire resistance | 650 °C conforming to IEC 60695-2-1 | |
| IP degree of protection | IP65 conforming to IEC 60529 | |
| IK degree of protection | IK09 conforming to EN 50102 | |
| Environmental characteristics (UV) | UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013 | |
| Overvoltage category | П | |
| Ambient air temperature for operation | -2560 °C | |

Packing Units

| _ | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 12.000 cm |
| Package 1 Width | 12.000 cm |
| Package 1 Length | 20.000 cm |
| Package 1 Weight | 515.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 9 |
| Package 2 Height | 22.500 cm |
| Package 2 Width | 34.500 cm |
| Package 2 Length | 41.000 cm |
| Package 2 Weight | 4.950 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 216 |
| Package 3 Height | 80.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 139.200 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >








Lower Impact Materials Transparency RoHS/REACh

Resource performance



25

Well-being performance

Rohs Exemption Information

Yes



Halogen Free Product

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |