

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type: 7CV2131A SIMOTICS SD - 132S - IM B3 - 2 p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data Safe Area

U	Δ / Y	f	P	P	I	n	M	M	η <sup>3)</sup>			cosφ <sup>3)</sup>			I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub>	M <sub>k</sub> /M <sub>N</sub>	IE-CL	
[V]±10%		[Hz]±5%	[kW]	[hp]	[A]	[1/min]	[kgf.m]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4					
Motordaten / Motor Data																			
415	Δ	50	7.50	-/-	13.00	2925	2.5	24.5	88.6	88.6	88.6	0.90	0.87	0.79	7.0	2.4	3.4	IE2	
IM B3 / IM 1001			FS 132S		63 kg		SF:1		IS 12615 / IEC 60034-1			-							
Environmental conditions : -20 °C - +50 °C / 1,000 m										Locked rotor time (hot / cold) : 10 s   15 s									

Mechanical data

Sound pressure level 50Hz   60Hz	75 dB(A)	80 dB(A)	External earthing terminal	Yes (standard)
Moment of inertia   Rotor GD <sup>2</sup>	0.0165 kg m <sup>2</sup>   0.0659 kgf.m <sup>2</sup>		Vibration severity grade	A (Standard)
Bearing DE   NDE	6208 2ZC3	6208 2ZC3	Insulation	155(F) utilized to 130(B)
bearing lifetime			Duty type	S1
L <sub>10mh</sub> F <sub>Rad max</sub> according catalogue 50 60Hz <sup>1)</sup>	20,000 h	16,000 h	Direction of rotation	Bidirectional
L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup>	50,000 h	40,000 h	Frame material	Cast iron
Type of bearing	Locating (fixed) bearing, NDE		Forced ventilation motor details	- / -
Relubrication interval/quantity DE   NDE	-/- g   -/- g -/- h		Net weight of the motor (IM B3)	63 kg
Type of construction	IM B3 / IM 1001		Rotor weight	13 kg
Degree of protection	IP55		Data of anti condensation heating	-/- V, -/- W
Lubricants	Esso Unirex N3		Coating (paint finish)	Standard paint finish
Regreasing device	- / -		Color, paint shade	RAL7030
Grease nipple	-/-		Motor protection	(A) without
Condensate drainage holes	Yes		Method of cooling	IC411 - Self ventilated, surface cooled

Terminal box



Terminal box position	Top	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Material of terminal box	Aluminium	Cable entry	2xM32x1.5
Type of terminal box	TB1 H04	Cable gland	2 Plugs
Contact screw thread	M5		
Max. cross-sectional area	10 mm <sup>2</sup>		

Notes:

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal  
M<sub>k</sub>/M<sub>N</sub> = locked rotor torque / torque nominal  
M<sub>k</sub>/M<sub>N</sub> = break down torque / nominal torque

3) Efficiency value is valid only for sinusoidal line supply operation.

1) L<sub>10mh</sub> according to DIN ISO 281 10/2010

Responsible department	Technical reference	Created by	Approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents	
IN LVM		SPC				
	Document type			Document status		
	Datasheet			Released		
	MLFB and Order Code			Document number		
	1LE7501-1CA13-5AA4			Revision	Creation date	Language   Page
© INNOMOTICS 2024				01	2024-09-27	en   1/1