

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type: 7CV3314B SIMOTICS SD - 315L - IM B3 - 4 p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL	
[V]±10%		[Hz]±5%	[kW]	[hp]	[A]	[1/min]	[kgf.m]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4					
Motordaten / Motor Data																			
415	Δ	50	160.00	-/-	267.00	1489	105.0	1026.0	95.9	96.1	95.8	0.87	0.85	0.78	7.7	3.0	3.2	IE3	
IM B3 / IM 1001			FS 315L		1028 kg		SF:1		IS 12615 / IEC 60034-1			-							
Environmental conditions : -20 °C - +50 °C / 1,000 m										Locked rotor time (hot / cold) : 15 s 25 s									

Mechanical data

Sound pressure level 50Hz 60Hz	80 dB(A)	83 dB(A)	External earthing terminal	Yes (standard)
Moment of inertia Rotor GD ²	3.4367 kg m ² 13.7469 kgf.m ²		Vibration severity grade	A (Standard)
Bearing DE NDE	NU 319	6319 C3 INS	Insulation	155(F) utilized to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad max} according catalogue 50 60Hz ¹⁾	20,000 h	16,000 h	Direction of rotation	Bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	-/-	-/-	Frame material	Cast iron
Type of bearing	Locating (fixed) bearing, NDE		Forced ventilation motor details	- / -
Relubrication interval/quantity DE NDE	40 g 40 g 6,000 h		Net weight of the motor (IM B3)	1028 kg
Type of construction	IM B3 / IM 1001		Rotor weight	305 kg
Degree of protection	IP55		Data of anti condensation heating	-/- V, -/- W
Lubricants	Esso Unirex N3		Coating (paint finish)	Standard paint finish
Regreasing device	Yes (standard)		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 71412 A		Motor protection	(A) without
Condensate drainage holes	Yes		Method of cooling	IC411 - Self ventilated, surface cooled

Terminal box

Terminal box position	Top	Cable diameter from ... to ...	38.0 mm - 45.0 mm
Material of terminal box	Cast iron	Cable entry	2xM63x1.5
Type of terminal box	TB1 Q01	Cable gland	2 Plugs
Contact screw thread	M12		
Max. cross-sectional area	185 mm ²		

Notes:			
I _A /I _N = locked rotor current / current nominal			
M _K /M _N = locked rotor torque / torque nominal			
M _K /M _N = break down torque / nominal torque			
3) Efficiency value is valid only for sinusoidal line supply operation.			
1) L _{10mh} according to DIN ISO 281 10/2010			

Responsible department IN LVM	Technical reference	Created by SPC	Approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	Document type Datasheet			Document status Released			
	MLFB and Order Code 1LE7503-3AB43-5AA4-Z			Document number			
© INNOMOTICS 2024	L22+L53			Revision 01	Creation date 2024-09-27		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS									
Motor type:		7CV3314B		SIMOTICS SD - 315L - IM B3 - 4 p					
Special design									
L22		Bearing design for increased cantilever forces			L53		Insulated bearing NDE		
Notes:									
Responsible department		Technical reference		Created by		Approved by		Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	
IN LVM				SPC				Link documents	
SIEMENS		Document type				Document status			
		Datasheet				Released			
		MLFB and Order Code				Document number			
		1LE7503-3AB43-5AA4-Z							
© INNOMOTICS 2024		L22+L53				Revision		Creation date	
						01		2024-09-27	
						Language		Page	
						en		2/2	