



PRODUCT-DETAILS

# AF16-30-01-11

## AF16-30-01-11 24-60V50/60HZ 20-60VDC

### Contactors



| General Information   |   |
|-----------------------|---|
| Extended Product Type | AF16-30-01-11   |
| Product ID            | 1SBL177001R1101   |
| EAN                   | 3471523110717   |
| Catalog Description   | AF16-30-01-11 24-60V50/60HZ 20-60VDC Contactor  |
| Long Description      | <p>The AF16-30-01-11 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and screw terminals, controlling motors up to 7.5 kW / 400 V AC (AC-3) or 10 hp / 480 V UL and switching power circuits up to 30 A (AC-1) or 30 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p> |

| Ordering               |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

| Popular Downloads        |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SBC101027M6801 |
| CAD Dimensional Drawing  | 2CDC001079B0201 |

| Dimensions                 |         |
|----------------------------|---------|
| Product Net Width          | 45 mm   |
| Product Net Depth / Length | 77 mm   |
| Product Net Height         | 86 mm   |
| Product Net Weight         | 0.27 kg |

| Technical  |  |
|--|--|
| Number of Main Contacts NO                               | 3  |
| Number of Main Contacts NC                               | 0  |
| Number of Auxiliary Contacts NO                          | 0  |
| Number of Auxiliary Contacts NC                          | 1  |
| Standards  | IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1  |
| Rated Operational Voltage                                | Auxiliary Circuit 690 V<br>Main Circuit 690 V  |
| Rated Frequency (f)                                      | Auxiliary Circuit 50 / 60 Hz<br>Control Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz  |
| Conventional Free-air Thermal Current (I <sub>th</sub> ) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 35 A<br>acc. to IEC 60947-5-1, $\Theta = 40\text{ }^{\circ}\text{C}$ 16 A |
| Rated Operational Current AC-1 (I <sub>e</sub> )         | (690 V) 40 °C 30 A<br>(690 V) 60 °C 30 A<br>(690 V) 70 °C 26 A   |
| Rated Operational Current AC-3 (I <sub>e</sub> )         | (415 V) 60 °C 18 A<br>(440 V) 60 °C 18 A<br>(500 V) 60 °C 15 A<br>(690 V) 60 °C 10.5 A<br>(380 / 400 V) 60 °C 18 A<br>(220 / 230 / 240 V) 60 °C 18 A   |
| Rated Operational Current AC-3e (I <sub>e</sub> )        | (415 V) 60 °C 18 A<br>(440 V) 60 °C 18 A<br>(500 V) 60 °C 15 A<br>(690 V) 60 °C 10.5 A<br>(380 / 400 V) 60 °C 18 A<br>(220 / 230 / 240 V) 60 °C 18 A   |
| Rated Operational Power AC-3 (P <sub>e</sub> )           | (400 V) 7.5 kW<br>(415 V) 9 kW<br>(440 V) 9 kW<br>(500 V) 9 kW<br>(690 V) 9 kW<br>(380 / 400 V) 7.5 kW<br>(220 / 230 / 240 V) 4 kW                     |
| Rated Operational Power AC-3e (P <sub>e</sub> )          | (415 V) 9 kW<br>(440 V) 9 kW<br>(500 V) 9 kW<br>(690 V) 9 kW<br>(380 / 400 V) 7.5 kW<br>(220 / 230 / 240 V) 4 kW                                       |
| Rated Operational  | (500 V) 2 A  |

|   |   |
|---|---|
| Current AC-15 ( $I_e$ )   | (690 V) 2 A<br>(24 / 127 V) 6 A<br>(220 / 240 V) 4 A<br>(400 / 440 V) 3 A   |
| Rated Short-time<br>Withstand Current Low<br>Voltage ( $I_{cw}$ ) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A<br>for 0.1 s 140 A<br>for 1 s 100 A   |
| Maximum Breaking<br>Capacity                                      | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 250 A<br>cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 106 A  |
| Maximum Electrical<br>Switching Frequency                         | (AC-1) 600 cycles per hour<br>(AC-15) 1200 cycles per hour<br>(AC-2 / AC-4) 300 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-13) 900 cycles per hour   |
| Rated Operational<br>Current DC-1 ( $I_e$ )                       | (110 V) 1-Pole, 40 °C 20 A<br>(110 V) 1-Pole, 60 °C 20 A<br>(110 V) 1-Pole, 70 °C 20 A<br>(110 V) 2 Poles in Series, 40 °C 30 A<br>(110 V) 2 Poles in Series, 60 °C 30 A<br>(110 V) 2 Poles in Series, 70 °C 26 A<br>(110 V) 3 Poles in Series, 40 °C 30 A<br>(110 V) 3 Poles in Series, 60 °C 30 A<br>(110 V) 3 Poles in Series, 70 °C 26 A<br>(220 V) 2 Poles in Series, 40 °C 20 A<br>(220 V) 2 Poles in Series, 60 °C 20 A<br>(220 V) 2 Poles in Series, 70 °C 20 A<br>(220 V) 3 Poles in Series, 40 °C 30 A<br>(220 V) 3 Poles in Series, 60 °C 30 A<br>(220 V) 3 Poles in Series, 70 °C 26 A<br>(72 V) 1-Pole, 40 °C 30 A<br>(72 V) 1-Pole, 60 °C 30 A<br>(72 V) 1-Pole, 70 °C 26 A<br>(72 V) 2 Poles in Series, 40 °C 30 A<br>(72 V) 2 Poles in Series, 60 °C 30 A<br>(72 V) 2 Poles in Series, 70 °C 26 A<br>(72 V) 3 Poles in Series, 40 °C 30 A<br>(72 V) 3 Poles in Series, 60 °C 30 A<br>(72 V) 3 Poles in Series, 70 °C 26 A |
| Rated Operational<br>Current DC-3 ( $I_e$ )                       | (110 V) 1-Pole, 40 °C 8 A<br>(110 V) 1-Pole, 60 °C 8 A<br>(110 V) 1-Pole, 70 °C 8 A<br>(110 V) 2 Poles in Series, 40 °C 30 A<br>(110 V) 2 Poles in Series, 60 °C 30 A<br>(110 V) 2 Poles in Series, 70 °C 26 A<br>(110 V) 3 Poles in Series, 40 °C 30 A<br>(110 V) 3 Poles in Series, 60 °C 30 A<br>(110 V) 3 Poles in Series, 70 °C 26 A<br>(220 V) 2 Poles in Series, 40 °C 8 A<br>(220 V) 2 Poles in Series, 60 °C 8 A<br>(220 V) 2 Poles in Series, 70 °C 8 A<br>(220 V) 3 Poles in Series, 40 °C 30 A<br>(220 V) 3 Poles in Series, 60 °C 30 A<br>(220 V) 3 Poles in Series, 70 °C 26 A<br>(72 V) 1-Pole, 40 °C 30 A<br>(72 V) 1-Pole, 60 °C 30 A<br>(72 V) 1-Pole, 70 °C 26 A<br>(72 V) 2 Poles in Series, 40 °C 30 A<br>(72 V) 2 Poles in Series, 60 °C 30 A<br>(72 V) 2 Poles in Series, 70 °C 26 A<br>(72 V) 3 Poles in Series, 40 °C 30 A<br>(72 V) 3 Poles in Series, 60 °C 30 A<br>(72 V) 3 Poles in Series, 70 °C 26 A       |
| Rated Operational<br>Current DC-5 ( $I_e$ )                       | (110 V) 1-Pole, 40 °C 4 A<br>(110 V) 1-Pole, 60 °C 4 A<br>(110 V) 1-Pole, 70 °C 4 A<br>(110 V) 2 Poles in Series, 40 °C 20 A  |

|  |   |
|--|---|
|  | (110 V) 2 Poles in Series, 60 °C 20 A<br>(110 V) 2 Poles in Series, 70 °C 20 A<br>(110 V) 3 Poles in Series, 40 °C 30 A<br>(110 V) 3 Poles in Series, 60 °C 30 A<br>(110 V) 3 Poles in Series, 70 °C 26 A<br>(220 V) 2 Poles in Series, 40 °C 4 A<br>(220 V) 2 Poles in Series, 60 °C 4 A<br>(220 V) 2 Poles in Series, 70 °C 4 A<br>(220 V) 3 Poles in Series, 40 °C 16 A<br>(220 V) 3 Poles in Series, 60 °C 16 A<br>(220 V) 3 Poles in Series, 70 °C 16 A<br>(72 V) 1-Pole, 40 °C 16 A<br>(72 V) 1-Pole, 60 °C 16 A<br>(72 V) 1-Pole, 70 °C 16 A<br>(72 V) 2 Poles in Series, 40 °C 30 A<br>(72 V) 2 Poles in Series, 60 °C 30 A<br>(72 V) 2 Poles in Series, 70 °C 26 A<br>(72 V) 3 Poles in Series, 40 °C 30 A<br>(72 V) 3 Poles in Series, 60 °C 30 A<br>(72 V) 3 Poles in Series, 70 °C 26 A |
| Rated Operational<br>Current DC-13 ( $I_e$ )     | (24 V) 6 A / 144 W<br>(48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W<br>(400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W<br>(600 V) 0.1 A / 60 W   |
| Rated Insulation Voltage<br>( $U_i$ )            | acc. to IEC 60947-4-1 690 V<br>acc. to IEC 60947-5-1 690 V<br>acc. to UL/CSA 600 V  |
| Rated Impulse<br>Withstand Voltage ( $U_{imp}$ ) | 6 kV  |
| Maximum Mechanical<br>Switching Frequency        | 3600 cycles per hour  |
| Rated Control Circuit<br>Voltage ( $U_c$ )       | 50 Hz 24 ... 60 V<br>60 Hz 24 ... 60 V<br>DC Operation 20 ... 60 V  |
| Operate Time                                     | Between Coil De-energization and NC Contact Closing 13 ... 98 ms<br>Between Coil De-energization and NO Contact Opening 11 ... 95 ms<br>Between Coil Energization and NC Contact Opening 38 ... 90 ms<br>Between Coil Energization and NO Contact Closing 40 ... 95 ms  |
| Mounting on DIN Rail                             | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715  |
| Mounting by Screws (not<br>supplied)             | 2 x M4 screws placed diagonally   |
| Connecting Capacity<br>Main Circuit              | Flexible with Ferrule 1/2x 0.75 ... 6 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 4 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 4 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 6 mm <sup>2</sup>  |
| Connecting Capacity<br>Auxiliary Circuit         | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>  |
| Connecting Capacity<br>Control Circuit           | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Rigid Solid 1/2x 1 ... 2.5 mm <sup>2</sup><br>Rigid Stranded 1/2x 1 ... 2.5 mm <sup>2</sup>  |
| Wire Stripping Length                            | Auxiliary Circuit 10 mm<br>Control Circuit 10 mm<br>Main Circuit 10 mm  |

|                      |   |
|----------------------|---|
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Terminal Type        | Screw Terminals   |

Technical UL/CSA

|  |  |
|--|--|
| Maximum Operating Voltage UL/CSA             | Main Circuit 600 V   |
| General Use Rating UL/CSA                    | (600 V AC) 30 A  |
| Horsepower Rating UL/CSA                     | (120 V AC) Single Phase 1-1/2 hp<br>(200 ... 208 V AC) Three Phase 5 hp<br>(220 ... 240 V AC) Three Phase 5 hp<br>(240 V AC) Single Phase 3 hp<br>(440 ... 480 V AC) Three Phase 10 hp<br>(550 ... 600 V AC) Three Phase 15 hp |
| Connecting Capacity Main Circuit UL/CSA      | Rigid Solid 1/2x 16-10 AWG<br>Rigid Stranded 1/2x 16-10 AWG  |
| Connecting Capacity Auxiliary Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG<br>Rigid Stranded 1/2x 18-14 AWG  |
| Connecting Capacity Control Circuit UL/CSA   | Rigid Solid 1/2x 18-14 AWG<br>Rigid Stranded 1/2x 18-14 AWG  |
| Tightening Torque UL/CSA                     | Auxiliary Circuit 11 in·lb<br>Control Circuit 11 in·lb<br>Main Circuit 13 in·lb  |

Environmental

|  |  |
|--|--|
| Ambient Air Temperature                    | Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C<br>Close to Contactor without Thermal O/L Relay -40 ... 70 °C<br>Close to Contactor for Storage -60 ... +80 °C    |
| Climatic Withstand                         | Category B according to IEC 60947-1 Annex Q  |
| Maximum Operating Altitude Permissible     | Without Derating 3000 m  |
| Resistance to Shock acc. to IEC 60068-2-27 | Closed, Shock Direction: B1 25 g<br>Open, Shock Direction: B1 5 g<br>Shock Direction: A 30 g<br>Shock Direction: B2 15 g<br>Shock Direction: C1 25 g<br>Shock Direction: C2 25 g |
| Resistance to Vibrations                   | 4g Closed Position & 2g Open position 5 ... 300 Hz   |

Material Compliance

|   |  |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658  |
| REACH Declaration                           | 2CMT2021-006202  |
| RoHS Information                            | 2CMT2021-006277  |
| RoHS Status                                 | Following EU Directive 2011/65/EU                          |
| Toxic Substances Control Act - TSCA         | 2CMT2023-006525  |
| WEEE B2C / B2B                              | Business To Business                                       |
| WEEE Category                               | 5. Small Equipment (No External Dimension More Than 50 cm) |

Certificates and Declarations

|                                     |  |
|-------------------------------------|--|
| ABS Certificate                     | ABS_20-2060694-PDA                         |
| BV Certificate                      | BV_2634H24898C0                            |
| CB Certificate                      | CB_SE-108879                               |
| CCC Certificate                     | CCC_2010010304445624                       |
| CQC Certificate                     | CQC2010010304445624<br>CQC2020010304298240 |
| Declaration of<br>Conformity - CCC  | 2020980304001253<br>2020980304001082       |
| Declaration of<br>Conformity - CE   | 1SBD250000U1000                            |
| Declaration of<br>Conformity - UKCA | 1SBD250031U1000                            |
| DNV Certificate                     | DNV_TAE00001AF-4                           |
| EAC Certificate                     | EAC_RU_FRME77B03447                        |
| GOST Certificate                    | GOST_POCCFR.ME77.B07175.pdf                |
| KC Certificate                      | KC_HW02016-15005C                          |
| LR Certificate                      | LRS_LR23403517TA-02                        |
| RINA Certificate                    | RINA_ELE240318XG                           |
| RMRS Certificate                    | RMRS_1802705280                            |
| UL Certificate                      | UL-US-2150887-5<br>UL-CA-2142658-5         |
| UL Listing Card                     | E312527                                    |

Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 87 mm         |
| Package Level 1 Depth /<br>Length | 79 mm         |
| Package Level 1 Height            | 47 mm         |
| Package Level 1 Gross<br>Weight   | 0.27 kg       |
| Package Level 1 EAN               | 3471523110717 |
| Package Level 2 Units             | box 27 piece  |
| Package Level 2 Width             | 250 mm        |
| Package Level 2 Depth /<br>Length | 300 mm        |
| Package Level 2 Height            | 315 mm        |
| Package Level 2 Gross<br>Weight   | 7.29 kg       |
| Package Level 3 Units             | 1296 piece    |

Classifications

|                                       |   |
|---------------------------------------|---|
| Object Classification<br>Code         | Q   |
| ETIM 4                                | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                                | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                                | EC000066 - Power contactor, AC switching  |
| ETIM 7                                | EC000066 - Power contactor, AC switching  |
| ETIM 8                                | EC000066 - Power contactor, AC switching  |
| eClass                                | V11.0 : 27371003                          |
| UNSPSC                                | 39121529                                  |
| IDEA Granular Category<br>Code (IGCC) | 4758 >> Iec Contactors                    |

|                    |         |
|--------------------|---------|
| E-Number (Finland) | 3705805 |
| E-Number (Sweden)  | 3211342 |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF16

