

[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors <100A](#) > A16-30-01 24V 50Hz / 2



♥ [ADD TO WISH LIST](#)

Share with your friends



Automation & Control

Genuine products

Dedicated
Support

Doorstep Delivery

Enquire Now

ABB

A16-30-01 24V 50Hz / 24V 60Hz Contactor

₹723.60 + ₹130.25 (GST 18%)

- 1 +

Buy Now

Add to Cart

More Offers available from [3 sellers](#) starting at
INR. 853.85

Pin Code

Calculate Shipping

Please enter your PIN Code to check the best offers

Product Id#: 1SBL181001R8101

[Be the first to review this product](#)



Sold and delivered by **PIGEON AGENCY**

A16 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, 1 built-in auxiliary contact, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

More about A16-30-01 24V 50Hz / 24V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	3
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-5-1, q = 40 °C 16 ampere, acc Contactors q = 40 °C 30 ampere
Coil Consumption	Average Holding Value 50 / 60 Hz 8 2 volt - am Value 50 Hz 74 volt - ampere, Average Pull-in V ampere
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NC Contact millisecond, Between Coil De-energization and ... 11 millisecond, Between Coil Energization ar ... 21 millisecond, Between Coil Energization ar
Rated Control Circuit Voltage (Uc)	50 Hz 24V; 60 Hz 24V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3

Enquire Now



Rated Operational Power AC-6b (Pe)	(230 / 240 V) 40 °C, 50 / 60 Hz 7.5 KVR, (230 / 7.5 KVR, (230 / 240 V) 70 °C, 50 / 60 Hz 6 KVR, 60 Hz 12.5 KVR, (400 / 415 V) 70 °C, 50 / 60 Hz °C, 50 / 60 Hz 12.5 KVR, (440 V) 40
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 4 KWT, (380 / 400 V) 7.5 KI V) 9 KWT, (500 V) 9 KWT, (690 V) 9 KWT
Rated Operational Current DC-13 (Ie)	(125 V) 1.1 / 138 ampere, (24 V) 6 / 144 ampere ampere, (48 V) 2.8 / 134 ampere, (72 V) 2 / 144
Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 17 ampere, (380 / 40 (415 V) 55 °C 17 ampere, (440 V) 55 °C 16 ampe ampere, (690 V) 55 °C 10 ampere
Rated Operational Current AC-15 (Ie)	(220 / 240 V) 4 ampere, (24 / 127 V) 6 ampere, (500 V) 2 ampere, (690 V) 2 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 30 ampere, (690 V) 55 °C 27 ampe ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x Ie AC-15
Rated Frequency Limits	25 ... 400 hertz
Rated Frequency (f)	Supply Circuit 50 60 hertz
Package Width	78 millimetre
Package Length	76 millimetre
Package Height	47 millimetre
Invoice Description	A16-30-01 24V 50Hz / 24V 60Hz Contactor
Product Range	A Contactors
Package Gross Weight	0.34 kilogram
Extended Product Type	A16-30-01 24V 50Hz / 24V 60Hz
Number of Aux Contacts NC	1

Enquire Now



Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 deg Contactor without Thermal O/L Relay (0.85 ... Celsius, Close to Contactor Fitted with Therm degree Celsius, Close to Contactor without T
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

[Download](#)

[Offers](#)

[Reviews](#)

Recently Viewed

			Enquire Now
A26-30-01 110V 50Hz / 110-120V 60Hz Contactor 1SBL241001R8401 ₹1,170.09	A26-30-01 220-230V 50Hz / 230-240V 60Hz Contactor 1SBL241001R8001 ₹1,222.48	A26-30-01 24V 50Hz / 24V 60Hz Contactor 1SBL241001R8101 ₹1,501.90	A4C

☐ [Write to Us](#)

1800 420 0707

COMPANY INFORMATION

AboutSell Our
Us WithSellers

BlogsExchange and
Returns Policy

Privacy Terms
Policy of Use

How to create a
Company Account

FAQ



@ contactabb.in@abb.com

Us

(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya
Industrial Area IV, Peenya 560058,
Bangalore, Karnataka, India.

 [Facebook](#)  [Twitter](#)

 [Linkedin](#)  [Youtube](#)

Copyright © 2025 ABB India Ltd. | Address: Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bang

Enquire Now

