

## PRODUCT-DETAILS

A16-22-00 220-230V 50Hz / 230-240V 60Hz

A16-22-00 220-230V 50Hz / 230-240V 60Hz

Contactor

"No longer for sale" replaced by



### General Information

Extended Product Type	A16-22-00 220-230V 50Hz / 230-240V 60Hz
Product ID	1SBL181501R8000
EAN	3471522052803
Catalog Description	A16-22-00 220-230V 50Hz / 230-240V 60Hz Contactor
Long Description	<p>A16 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting...</p> <p>The A... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 2 N.O. + 2 N.C. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.</p>

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SBL171501R8000

### Popular Downloads

Data Sheet, Technical	1SBC100122C0202_Ch02
-----------------------	----------------------

## Information

## Instructions and Manuals

FPTC407721P0001

## Dimensions

Product Net Width	44 mm
Product Net Depth / Length	74 mm
Product Net Height	74 mm
Product Net Weight	0.34 kg

## Technical

Number of Main Contacts NO	2
Number of Main Contacts NC	2
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Standards	Devices complying with international standards IEC 947-1 / 947-4-1, and European standards EN 60 947-1 / 60 947-4-1. Electromagnetic compatibility (EMC) acc. to amendment A11 to IEC 947-1, EN 60 947-1 and amendment 2 to IEC 947-4-1
Rated Operational Voltage	Main Circuit 690 V
Rated Frequency (f)	Control Circuit 50 / 60 Hz
Conventional Free-air Thermal Current ( $I_{th}$ )	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40^\circ\text{C}$ 30 A
Rated Operational Current AC-1 ( $I_e$ )	(690 V) 40 °C 30 A (690 V) 55 °C 27 A (690 V) 70 °C 23 A
Rated Breaking Capacity AC-3	8 x $I_e$ AC-3
Rated Making Capacity AC-3	10 x $I_e$ AC-3
Short-Circuit Protective Devices	gG Type Fuses 32 A
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 140 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 30 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A
Maximum Breaking Capacity	$\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 250 A $\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 90 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour
Rated Insulation Voltage ( $U_i$ )	acc. to IEC 60947-4-1 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage ( $U_c$ )	50 Hz 220 ... 230 V 60 Hz 230 ... 240 V
Coil Consumption	Average Holding Value 50 / 60 Hz 8 V·A Average Pull-in Value 50 Hz 74 V·A

	Average Pull-in Value 60 Hz 70 V·A Holding at Max. Rated Control Circuit Voltage 50 Hz 8 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 8 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 2 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 70 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 80 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 9 ... 16 ms Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NC Contact Opening 7 ... 21 ms Between Coil Energization and NO Contact Closing 10 ... 26 ms
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting by Screws (not supplied)	2 x M4 screws placed diagonally
Connecting Capacity Main Circuit	Flexible with Cable End 0.75 ... 2.5 mm² Rigid Cable 1 ... 4 mm²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm² Rigid Cable 1 ... 4 mm²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 3.5 (+,-) pozidriv 2 screws with cable clamp
Terminal Type	Screw Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 30 A
------------------------------	-----------------

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air (0.85 ... 1.1 Uc) -40 ... +55 °C Near Contactor for Operation in Free Air (Uc) -40 ... 70 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Closed, Shock Direction: B1 10 g Open, Shock Direction: B1 5 g Shock Direction: A 20 g Shock Direction: B2 15 g Shock Direction: C1 20 g Shock Direction: C2 20 g

Material Compliance

RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

BV Certificate	BV_2634H07559E0
CB Certificate	CB_CN44759
CCC Certificate	CCC_2018010304059156 CCC_2004010309130463

CQC Certificate	CQC2013010304615753 CQC2018010304059156 CQC2004010309130463
CSA Certificate	CSA_1041746
Declaration of Conformity - CCC	2020980304001607 2020980304001616 2020980304001229
Declaration of Conformity - CE	1SBD250802U1000
Declaration of Conformity - UKCA	1SBD250819U1000
DNV Certificate	DNV-GL_TAE00000TX
DNV GL Certificate	DNV-GL_TAE00000TX
EAC Certificate	EAC_RU C-FR ME77 B03599
LR Certificate	LRS_9830011E4
RINA Certificate	RINA_ELE172319XG001
RMRS Certificate	RMRS_0507015250
UL Certificate	UL_20160205-E312527-10-2
UL Listing Card	UL_E312527

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	78 mm
Package Level 1 Depth / Length	76 mm
Package Level 1 Height	47 mm
Package Level 1 Gross Weight	0.34 kg
Package Level 1 EAN	3471522052803
Package Level 2 Units	box 63 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	21.42 kg
Package Level 3 Units	1220 piece

## Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Power contactor, AC switching
eClass	V11.0 : 27371003
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4760 >> Lighting Contactors

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → A Contactors

