



PRODUCT-DETAILS

UA26-30-10 110V 50Hz / 110-120V 60Hz
UA26-30-10 110V 50Hz / 110-120V 60Hz
Contactor



| General Information | |
|-----------------------|--|
| Extended Product Type | UA26-30-10 110V 50Hz / 110-120V 60Hz |
| Product ID | 1SBL241022R8410 |
| EAN | 3471522069849 |
| Catalog Description | UA26-30-10 110V 50Hz / 110-120V 60Hz Contactor |
| Long Description | <p>The UA26-30-10 110V 50Hz / 110-120V 60Hz is a 3-pole contactors for capacitor switching, can be used for the switching of capacitor banks whose inrush current peaks are less than or equal to 100 times nominal rms current. The table below gives the permissible powers according to operational voltage and temperature close to the contactor. It also specifies the maximum peak current \hat{I} values accepted by the contactor. The capacitors must be discharged (maximum residual voltage at terminals ≤ 50 V) before being re-energized when the contactors are making. In these conditions, electrical durability of contactors is equal to 100 000 operating cycles. The UA.. series 3-pole contactors are of the block type design. - Main poles and auxiliary contacts: 3 main poles, 1 built-in auxiliary contact - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.</p> |

| Ordering | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC101140C0203 |
| Instructions and Manuals | FPTC407722P0001 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 54 mm |
| Product Net Depth / Length | 93.6 mm |
| Product Net Height | 90 mm |
| Product Net Weight | 0.6 kg |

Technical

| | |
|---|---|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 1 |
| Number of Auxiliary Contacts NC | 0 |
| Standards | IEC/EN 60947-1, IEC/EN 60947-4-1 |
| Rated Operational Voltage | Auxiliary Circuit 690 V Main Circuit 690 V |
| Rated Frequency (f) | Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current (I_{th}) | acc. to IEC 60947-5-1, $\Theta = 40^\circ\text{C}$ 16 A |
| Rated Operational Power AC-6b (P_e) | (230 / 240 V) 40 °C, 50 / 60 Hz 12 kvar (230 / 240 V) 55 °C, 50 / 60 Hz 11 kvar (230 / 240 V) 70 °C, 50 / 60 Hz 8.5 kvar (400 / 415 V) 40 °C, 50 / 60 Hz 20 kvar (400 / 415 V) 70 °C, 50 / 60 Hz 14.5 kvar (400 / 415 V) 55 °C, 50 / 60 Hz 18.5 kvar (440 V) 40 °C, 50 / 60 Hz 22 kvar (440 V) 55 °C, 50 / 60 Hz 20 kvar (440 V) 70 °C, 50 / 60 Hz 16 kvar (500 / 550 V), 40 °C, 50 / 60 Hz 22 kvar (500 / 550 V) 55 °C, 50 / 60 Hz 22 kvar (500 / 550 V) 70 °C, 50 / 60 Hz 19.5 kvar (690 V) 40 °C, 50 / 60 Hz 30 kvar (690 V) 55 °C, 50 / 60 Hz 30 kvar (690 V) 70 °C, 50 / 60 Hz 25 kvar |
| Rated Operational Current AC-15 (I_e) | (500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A |
| Short-Circuit Protective Devices | Auxiliary Circuit - gG Type Fuses 10 A gG Type Fuses 1.5 ... 1.8 A |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | for 0.1 s 140 A for 1 s 100 A |

| | |
|--|---|
| Maximum Breaking Capacity | cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 420 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 170 A |
| Rated Operational Current DC-13 (I _e) | (24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 2 / 144 W (110 V) 1.1 A / 121 W (125 V) 1.1 / 138 W (220 V) 0.55 A / 121 W (250 V) 0.55 / 138 W |
| Rated Insulation Voltage (U _i) | acc. to IEC 60947-4-1 1000 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V |
| Rated Impulse Withstand Voltage (U _{imp}) | 8 kV |
| Maximum Mechanical Switching Frequency | 3600 cycles per hour |
| Rated Control Circuit Voltage (U _c) | 50 Hz 110 V 60 Hz 110 ... 120 V |
| Coil Consumption | Average Holding Value 50 / 60 Hz 12 V-A Average Pull-in Value 50 Hz 120 V-A Average Pull-in Value 60 Hz 120 V-A Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V-A Holding at Max. Rated Control Circuit Voltage 50 Hz 3 W Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 3 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 120 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 140 V-A |
| Operate Time | Between Coil De-energization and NO Contact Opening 4 ... 11 ms Between Coil Energization and NO Contact Closing 8 ... 21 ms |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting by Screws (not supplied) | 2 x M4 screws placed diagonally |
| Connecting Capacity Main Circuit | Flexible with Cable End 0.75 ... 4 mm ² Rigid Cable 1.5 ... 6 mm ² |
| Connecting Capacity Auxiliary Circuit | Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ² |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Connecting Terminals (delivered in open position) Main Poles | M 4 (+,-) pozidriv 2 screws with cable clamp |
| Terminal Type | Screw Terminals |

Environmental

| | |
|--|---|
| Ambient Air Temperature | Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air (0.85 ... 1.1 U _c) -40 ... +55 °C Near Contactor for Operation in Free Air (U _c) -40 ... 70 °C |
| Climatic Withstand | acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II |
| Maximum Operating Altitude Permissible | Without Derating 3000 m |

Material Compliance

| | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2021-006202 |

| | |
|-------------------------------------|--|
| RoHS Information | 2CMT2021-006277 |
| RoHS Status | Following EU Directive 2011/65/EU |
| Toxic Substances Control Act - TSCA | 2CMT2023-006525 |
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Certificates and Declarations

| | |
|----------------------------------|--|
| CB Certificate | CB_CN64164-A1_1 |
| CCC Certificate | CCC_2003010304060095 CCC_2008010304261926 |
| CQC Certificate | CQC2003010304060095 CQC2008010304261926 |
| CSA Certificate | CSA_1033838_LR056745 |
| Declaration of Conformity - CCC | 2020980304001610 2020980304001217 |
| Declaration of Conformity - CE | 1SBD250805U1000 |
| Declaration of Conformity - UKCA | 1SBD250822U1000 |
| GOST Certificate | GOST_POCCFRME77B07175 |
| UL Certificate | UL-US-L312527-1103-61017991-2 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 101 mm |
| Package Level 1 Depth / Length | 115 mm |
| Package Level 1 Height | 61 mm |
| Package Level 1 Gross Weight | 0.6 kg |
| Package Level 1 EAN | 3471522069849 |
| Package Level 2 Units | box 63 piece |
| Package Level 2 Width | 300 mm |
| Package Level 2 Depth / Length | 245 mm |
| Package Level 2 Height | 308 mm |
| Package Level 2 Gross Weight | 37.8 kg |
| Package Level 3 Units | 576 piece |

Classifications

| | |
|----------------------------|---------------------------------------|
| Object Classification Code | Q |
| ETIM 4 | EC001079 - Capacitor magnet contactor |
| ETIM 5 | EC001079 - Capacitor magnet contactor |
| ETIM 6 | EC001079 - Capacitor contactor |
| ETIM 7 | EC001079 - Capacitor contactor |
| ETIM 8 | EC001079 - Capacitor contactor |
| eClass | V11.0 : 27371006 |
| UNSPSC | 39121529 |
| IDEA Granular Category | 4756 >> Capacitor magnet contactor |

Code (IGCC)

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → UA and UA..RA Contactors → UA26

