

[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors < 100A](#) > A26-40-00 400-415V 50Hz / 4



Share with your friends



Automation & Control

# A26-40-00 400-415V 50Hz / 415-440V 60Hz Contactor

Out of stock

Upon Request

Product Id#: 1SBL241201R8600

[Be the first to review this product](#)

A26 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The A... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Enquire Now



More about A26-40-00 400-415V 50Hz / 415-440V 60Hz Contactor

ABB

Genuine products

Dedicated Support

Doorstep Delivery

Technical Specification

eMart

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	4
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 300 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors q = 40
Coil Consumption	Holding at Max. Rated Control Circuit Voltage Holding at Max. Rated Control Circuit Voltage Pull-in at Max. Rated Control Circuit Voltage 50 Pull-in at Max. Rated Control Circuit Voltage
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 690 volt
Operate Time	Between Coil De-energization and NO Contact millisecond, Between Coil Energization and NO millisecond
Rated Control Circuit Voltage (Uc)	50 Hz 400-415V; 60 Hz 415-440V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3
Rated Operational Power AC-3 (Pe)	(220 / 230 / 240 V) 6.5 KWT, (380 / 400 V) 11 K V) 15 KWT, (500 V) 15 KWT
Rated Operational Current AC-3 (Ie)	(220 / 230 / 240 V) 55 °C 26 ampere, (380 / 400 (415 V) 55 °C 26 ampere, (440 V) 55 °C 26 amp ampere, (690 V) 55 °C 17 ampere
Rated Operational Current AC-1 (Ie)	(690 V) 40 °C 45 ampere, (690 V) 55 °C 40 amp ampere
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x Ie AC-3

Enquire Now



Rated Frequency Limits	25 ... 400 hertz
Package Width	101 millimetre
Package Length	115 millimetre
Package Height	61 millimetre
Invoice Description	A26-40-00 400-415V 50Hz / 415-440V 60Hz C
Product Range	A Contactors
Package Gross Weight	0.61 kilogram
Extended Product Type	A26-40-00 400-415V 50Hz / 415-440V 60Hz
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 deg Contactor for Operation in Free Air (Uc) -40 ... Contactor for Operation in Free Air (0.85 ... 1.1 Celsius
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Bulgaria (BG) - Imported by ABB India Limited

Enquire Now

[Download](#)

[Reviews](#)

## Recently Viewed




<div></div> <div><p><u>A26-22-00 110V 50Hz / 110-120V 60Hz</u></p><p>1SBL241501R8400</p><p>₹2,508.00</p></div>	<div></div> <div><p><u>A26-22-00 24V 50Hz / 24V 60Hz Contactor</u></p><p>1SBL241501R8100</p><p>₹2,914.00</p></div>	<div></div> <div><p><u>A50-40-00 220-230V 50Hz / 230-240V 60Hz Contactor</u></p><p>1SBL351201R8000</p><p>₹6,012.34</p></div>	Al
--	--	---	----


Write to Us


1800 420 0707


@ [contactabb.in@abb.com](mailto:contactabb.in@abb.com)  
(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya  
Industrial Area IV, Peenya 560058,  
Bangalore, Karnataka, India.

Facebook

Twitter

Linkedin

Youtube

COMPANY

INFORMATION

About Us

Sell Our Us

Our With Sellers

Blogs

Exchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

Enquire Now

Copyright © 2025 ABB India Ltd. | Address: Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bang

https://shop.in.abb.com/1sbl241201r8600/a26-40-00-400-415v-50hz-415-440v-60hz-contactor.html?srsltid=AfmBOoq\_7Wf6-awOvQi0g8wkHdJ19jJ4F...

4/4