


[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors < 100A](#) > A63-30-00 24V 50Hz / 2



♥ [ADD TO WISH LIST](#)

Share with your friends

Genuine products

Dedicated  
Support

Doorstep Delivery

[eMart](#)

Enquire Now

Automation & Control

# A63-30-00 24V 50Hz / 24V 60Hz Contactor

**₹5120.34** + ₹921.66 (GST 18%)

- 1 +

[Buy Now](#)

[Add to Cart](#)

More Offers available from [3 sellers](#) starting at  
INR. 6042.00

Pin Code

[Calculate Shipping](#)

Please enter your PIN Code to check the best offers

Product Id#: 1SBL371001R8100

[Be the first to review this product](#)



Sold and delivered by **Vihaan Technologies**

A63 contactors are mainly used for controlling 3-phase motors and generally for controlling power circuits up to 690 V AC / 1000 V AC or 220 V DC. The contactors can also be used for many other applications such as isolation, capacitor switching, lighting. The A... series 1-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

More about A63-30-00 24V 50Hz / 24V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	3
Compatibility	A Contactors
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	AC-1 600 cycles per hour, AC-2 / AC-4 150 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors q = 40
Coil Consumption	Average Holding Value 50 / 60 Hz 18 5.5 volt - Value 50 Hz 190 volt - ampere, Average Pull-in ampere
Terminal Type	Screw Terminals
Rated Operational Voltage	Main Circuit 1000 volt
Operate Time	Between Coil De-energization and NO Contact millisecond, Between Coil Energization and NO millisecond
Rated Control Circuit Voltage (Uc)	50 Hz 24V; 60 Hz 24V
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x Ie AC-3

Enquire Now








[Download](#)

[Offers](#)

[Reviews](#)

Recently Viewed

 <p><u>A75-30-00 24V 50Hz / 24V 60Hz Contactor</u> 1SBL411001R8100 <b>Out of Stock</b></p>	 <p><u>A75-30-00 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL411001R8600 <b>Out of Stock</b></p>	 <p><u>A9-40-00 24V 50Hz / 24V 60Hz Contactor</u> 1SBL141201R8100 <b>Out of Stock</b></p>	<p><u>A9-</u></p>
---	---	--	-------------------

Enquire Now

☐ [Write to Us](#)

1800 420 0707

@ [contactabb.in@abb.com](mailto:contactabb.in@abb.com)

(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bangalore, Karnataka, India.

[Facebook](#)

[Twitter](#)

[Linkedin](#)

[Youtube](#)

COMPANY

INFORMATION

About Us

Sell Our With Sellers Us

Blogs

Exchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

