



PRODUCT-DETAILS

# CA5-22E

## CA5-22E Auxiliary Contact Block



General Information	
Extended Product Type	CA5-22E
Product ID	1SBN010040R1022
EAN	3471522121103
Catalog Description	CA5-22E Auxiliary Contact Block
Long Description	CA5-22E is a 4-pole front mounted auxiliary contact block equipped with screw terminals. CA5-..E version offers terminal assortment matching the marking of 3-pole A serie contactors: A..-30-00, A..-40-00, A..-22-00. CA5-22E is available with 2 N.O. and 2 N.C. instantaneous contacts for standard industrial environments.

Ordering	
Minimum Order Quantity	2 piece
Customs Tariff Number	85389099

Popular Downloads	
Data Sheet, Technical Information	1SBC100214C0202

Instructions and Manuals	1SBC101012M5501
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	44 mm
Product Net Depth / Length	39 mm
Product Net Height	47 mm
Product Net Weight	0.06 kg

Technical

Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	2
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I <sub>e</sub> )	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency	1200 cycles per hour
Rated Operational Current DC-13 (I <sub>e</sub> )	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.3 / 75 W
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Mechanical Durability	10 million 3 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Terminal Type	Screw Terminals
Suitable For	AF45 AF50 AF63 AF75 AF95B GAF75 A9 A16 A26 A45 A50 A63

A75  
A95  
A110  
AL9  
AL16  
AL26  
AE45  
AE50  
AE63  
AE75  
TAL9  
TAL16  
TAL26  
TAE45  
TAE50  
TAE75  
GA75  
GAE75  
UA50  
UA63  
UA75  
UA95  
UA110

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_SE_62119A1
CCC Certificate	CCC_2015010304800518
CQC Certificate	CQC2015010304800518 CQC2004010305133985
CSA Certificate	CSA_1033838
Declaration of Conformity - CCC	2020980304001627 2020980305001185
Declaration of Conformity - CE	1SBD250809U1000
Declaration of Conformity - UKCA	1SBD250826U1000
DNV GL Certificate	DNV_GL_TAE00001UT
EAC Certificate	EAC_RU C-FR ME77 B03391
GOST Certificate	GOST_POCCFRME77B07175
RINA Certificate	RINA_ELE172319XG001
UL Certificate	UL_071301E48139

Container Information

Package Level 1 Units	box 2 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	129.5 mm

Package Level 1 Height	43 mm
Package Level 1 Gross Weight	0.12 kg
Package Level 1 EAN	3471522121103
Package Level 2 Units	box 200 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	12 kg
Package Level 3 Units	3600 piece

Classifications

Object Classification Code	K
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block
E-Number (Finland)	3709197

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

