

PRODUCT-DETAILS

T5S 630 PR221DS-I In=630 3p F F

T5S 630 PR221DS-I In=630 3p F F



| General Information   |  |
|-----------------------|--|
| Extended Product Type | T5S 630 PR221DS-I In=630 3p F F  |
| Product ID            | 1SDA054405R1   |
| EAN                   | 8015644555030  |
| Catalog Description   | T5S 630 PR221DS-I In=630 3p F F  |
| Long Description      | C.BREAKER TMAX T5S 630 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-I R 630 |

| Circular Value                              |                 |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Toxic Substances Control Act - TSCA         | 9AKK108467A8326 |

| Environmental             |                                   |
|---------------------------|-----------------------------------|
| Environmental Information | 9AKK10103A1056<br>9AKK108467A6707 |
| REACH Declaration         | 9AKK108466A1425                   |
| RoHS Information          | 9AKK108466A1424                   |



|   |  |
|---|--|
| Circuit Breaking Capacity (I <sub>cu</sub> )      | (230 V AC) 85 kA<br>(380 V AC) 50 kA<br>(400 V AC) 50 kA<br>(415 V AC) 50 kA<br>(440 V AC) 40 kA<br>(500 V AC) 30 kA<br>(690 V AC) 25 kA |
| Rated Uninterrupted Current (I <sub>u</sub> )     | 630 A  |
| Release   | PR221DS-I  |
| Release Type                                      | EL   |
| Short-Circuit Performance Level                   | S  |
| Standards   | IEC  |
| Sub-type  | T5   |
| Suitable For                                      | T5   |
| Suitable for Product Class                        | Moulded Case Circuit Breakers  |
| Terminal Connection Type                          | Fixed Circuit-Breakers<br>Front  |
| Test Voltage Max (U <sub>test</sub> )             | 3500 V   |
| Test Voltage at Industrial Frequency for 1 Minute | 3500 V   |
| Version   | F  |

Certificates and Declarations

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210004D0203 |
| Declaration of Conformity - CE    | 9AKK106713A5539 |
| GL Certificate                    | 1SDL000163R0062 |
| Instructions and Manuals          | 1SDH000437R0001 |
| Instructions and Manuals (Part 2) | ITSCE-RH0100001 |

Classifications

|                            |  |
|----------------------------|--|
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q  |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                     | V11.1 : 27370409   |

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

