


PRODUCT-DETAILS

SOR T4-T5-T6 24...30 Vac/dc

SOR T4-T5-T6 24...30 Vac/dc



### General Information

Extended Product Type	SOR T4-T5-T6 24...30 Vac/dc
Product ID	1SDA054863R1
EAN	8015644559915
Catalog Description	SOR T4-T5-T6 24...30 Vac/dc
Long Description	SHUNT OPENING RELEASE 24...30V AC-DC T4-T5-T6

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

### Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering	
E-Number (Finland)	3655617
EAN	8015644559915
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensions	
Product Net Weight	0.136 kg

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	110 mm
Package Level 1 Height	60 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Gross Weight	0.143 kg
Package Level 1 EAN	8015644559915

Additional Information	
Configuration Type	Loose or configurable
Current Type	AC/DC
Product Main Type	Accessories for Tmax T
Product Name	Accessory
Product Type	Accessory
Rated Voltage (U <sub>r</sub> )	24 ... 30 V AC 24 ... 30 V DC
Standards	IEC
Suitable For	T4, T5, T6
Suitable for Product Class	SACE Tmax T

Certificates and Declarations	
Data Sheet, Technical Information	1SDC210015D0208 1SDC210300D0201
Declaration of Conformity - CE	Refer to the EU Declaration of the relative Circuit Breaker
Instructions and Manuals	1SDH000436R0602

Classifications	
ETIM 7	EC002483 - Switch spool for power circuit breaker
ETIM 8	EC002483 - Switch spool for power circuit breaker
ETIM 9	EC002483 - Switch spool for power circuit breaker
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370421

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Accessories for Tmax T

