

PRODUCT-DETAILS

T6S 630 TMA 630-6300 3p F F  
T6S 630 TMA 630-6300 3p F F



General Information	
Extended Product Type	T6S 630 TMA 630-6300 3p F F
Product ID	1SDA060204R1
EAN	8015644626624
Catalog Description	T6S 630 TMA 630-6300 3p F F
Long Description	C.BREAKER TMAX T6S 630 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 630 I3=3150...6300 A

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326

Environmental	
Environmental Information	9AKK10103A1058 9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424



Voltage (I <sub>cw</sub> )	
Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 45 kA (500 V AC) 35 kA (690 V AC) 22 kA (250 V DC) 2 Poles in Series 50 kA (500 V DC) 2 Poles in Series 35 kA (750 V DC) 3 Poles in Series 20 kA
Rated Uninterrupted Current (I <sub>u</sub> )	630 A
Release	TMA
Release Type	TM
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	T6
Suitable For	T6
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Test Voltage Max (U <sub>test</sub> )	3500 V
Version	F

Certificates and Declarations

Data Sheet, Technical Information	1SDC210015D0201
Declaration of Conformity - CE	9AKK106713A5538
Instructions and Manuals	1SDH000511R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39121100
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

