

PRODUCT-DETAILS

# XT1C 160 TMD 40-450 3p F F

## XT1C 160 TMD 40-450 3p F F



### General Information

Extended Product Type	XT1C 160 TMD 40-450 3p F F
Product ID	1SDA067393R1
EAN	8015644012175
Catalog Description	XT1C 160 TMD 40-450 3p F F
Long Description	C.BREAKER TMAX XT1C 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 40-450 A

### ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

### Circular Value

Circular Design	Design for Closing Resource Loops - Standard EN45555 - 55.9 %
Principles Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2347
Group Waste to Landfill	UL 2799 Zero Waste To Landfill Validation available

Target	
Toxic Substances	9AKK108467A8326
Control Act - TSCA	

Eco Transparency

Environmental Product	9AKK108468A1890
Declaration - EPD	9AKK108468A7793

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	8a91ff6a-ad35-4fb5-a92a-df6404a582cb Italy (IT)
Simplified SCIP	52ef1d57-7ac3-4b6f-a7e4-e82a028ffb83 Netherlands (NL) 74d485f3-103e-4d7a-8443-1f7ad4022261 Netherlands (NL) f4830c59-0293-41c0-b6c6-bbc224ef389e Germany (DE) 75045930-dcf8-4bdf-a8a6-b1d7536722b0 Denmark (DK) 00d5e05b-73de-4ffd-ada4-75fe59753d1b Germany (DE) a3bb56c5-c825-461f-b74a-af460f0a46b3 Croatia (HR) 511b521b-ee85-4c5d-bc0a-7a79e53ee659 Czech Republic (CZ) 6c056f27-91fa-4473-854f-037e49936562 Netherlands (NL) 4019c24c-8691-4202-9180-e5d03adce627 Netherlands (NL) 48db9e10-b526-4ac0-aae6-d10ceea229d1 Estonia (EE) ba95b5e4-99d5-4eea-b2c9-cb155dd74fa9 Greece (GR) c445fb07-7d15-41b6-a68d-cdb076abe0f1 Portugal (PT) 2bbe0591-3502-4ecc-b98b-6a391f7c3659 Bulgaria (BG) eb299f83-c903-4a3c-b98c-1d1fc6bbcadb Sweden (SE) 6abe2cd0-f062-4d83-9004-c331378e8e51 Poland (PL) e62cb378-2733-4350-aa9c-3b6ed41c578f France (FR) 30e1b010-9328-4a58-8902-080379a87c23 Sweden (SE) be0d0faf-5974-449f-b370-495cba09cb01 Germany (DE) 9140d5d7-7c67-405b-bf7e-5475de634beb Germany (DE) 23f70161-83b5-42b7-b046-4553eb6db904 Spain (ES) 7cce477e-45c8-445e-9a44-47829e0653e7 Netherlands (NL) d5142b24-b2c5-442e-92f1-34be6bf004b6 Poland (PL) 0da3aafb-d5a7-44a0-866d-3774ab59123e Poland (PL) 9d65d086-3f78-4165-b15a-c20f5c9a033b Finland (FI) 167b4a8a-f6f6-4ac1-b303-632a0bd3431b Norway (NO) 3b58e72f-8f59-4998-b549-8ee112e84c38 France (FR)

Ordering

Order Code US and Canada	XT1CE3040AFF000XXX
E-Number (Finland)	3638775
EAN	8015644012175
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	76.2 mm
Product Net Height	130 mm
Product Net Depth / Length	70 mm

Product Net Weight	1.1 kg
--------------------	--------

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	128 mm
Package Level 1 Height	135 mm
Package Level 1 Depth / Length	143 mm
Package Level 1 Gross Weight	1.12 kg
Package Level 1 EAN	8015644012175

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Connecting Capacity Main Circuit	Busbar 45.5 ... 80 mm²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 2.6 W
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	Automatic Circuit Breaker
Rated Current (I <sub>n</sub> )	40 A
Rated Frequency (f)	50 / 60 Hz
Rated Voltage (U <sub>r</sub> )	690 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	8 kV
Rated Instantaneous Short-Circuit Current Setting (I <sub>i</sub> )	450 A
Rated Insulation Voltage (U <sub>i</sub> )	800 V
Rated Operational Voltage	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	(220 V AC) 40 kA (230 V AC) 40 kA (240 V AC) 40 kA (380 V AC) 25 kA (415 V AC) 25 kA (440 V AC) 12.5 kA (500 V AC) 9 kA (525 V AC) 8 kA (690 V AC) 4 kA (250 V DC) 2 Poles in Series 25 kA (500 V DC) 3 Poles in Series 25 kA
Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )	(220 V AC) 40 kA (230 V AC) 40 kA (240 V AC) 40 kA

	(380 V AC) 25 kA
	(415 V AC) 25 kA
	(440 V AC) 25 kA
	(500 V AC) 18 kA
	(525 V AC) 8 kA
	(690 V AC) 4 kA
	(250 V DC) 2 Poles in Series 25 kA
	(500 V DC) 3 Poles in Series 25 kA
Rated Uninterrupted Current (I <sub>u</sub> )	160 A
Recommended Screw Driver	Main Circuit M6
Release	TMD
Release Type	TM
Setting Range	28...40 A
Short-Circuit Performance Level	C
Standards	IEC
Sub-type	XT1
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	6 N·m
Version	F
CAD Dimensional Drawing	1SDH001295R0008

Certificates and Declarations

ATEX Certificate	No certification needed
Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5532
GL Certificate	1SDL000163R0103
LR Certificate	1SDL000163R0100
UL Certificate	No certification needed
VDE Certificate	No certification needed
Dimension Diagram	1SDH000719R0100
Mechanical Drawings	1SDH000719R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000719R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

---

## Categories

---

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

