


PRODUCT-DETAILS

XT3S 250 TMD 200-2000 3p F F
XT3S 250 TMD 200-2000 3p F F



General Information

Extended Product Type	XT3S 250 TMD 200-2000 3p F F
Product ID	1SDA068220R1
EAN	8015644021269
Catalog Description	XT3S 250 TMD 200-2000 3p F F
Long Description	C.BREAKER TMAX XT3S 250 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMD R 200-2000 A

ABB EcoSolutions

ABB EcoSolutions	Yes
------------------	-----

Circular Value

Circular Design Principles	Design for Closing Resource Loops - Standard EN45555 - 56.6 %
Recyclability Rate	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	9AKK108468A2350
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available
Toxic Substances Control Act - TSCA	9AKK108467A8326

Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A2294
	9AKK108468A7794

Environmental

Environmental Information	9AKK108467A6707
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	d8122831-ef02-4136-a308-0ca35e4debc5 Italy (IT)
Simplified SCIP	a5cfc034-ff32-4da3-a1e0-ae34b787720b Czech Republic (CZ) 84a0e6c1-a659-4e4d-8938-ce4bab634d23 Poland (PL) 4032aa7c-fa89-44a3-9cdd-1e3f05541095 Netherlands (NL) b53576df-99cc-4638-a303-28f81665f6c8 Netherlands (NL) 3409c441-b5e4-4d4e-a671-837f877c4ec4 Estonia (EE) 9dc6f330-f0e3-4e0e-ad5e-6daf21374176 Greece (GR) 9294771f-6555-4dc6-8106-e9e9f0d74ae1 Portugal (PT) b02f56c3-1702-4f25-9f05-23010c00667c Bulgaria (BG) 7c176d9b-5bfa-4ae4-8f7b-b483948fb74c Sweden (SE) e9e18279-8f22-4ebe-a9ab-b2d29d25840b Poland (PL) bb59b0af-96db-4749-ae05-a5e1fbec0393 France (FR) 4333ea09-1e7c-40e1-a851-f904604b7c13 Sweden (SE) 111e81b2-3136-44b3-87e7-ee30207a824f Germany (DE) 4600d34c-2fef-40e0-91f5-196317e081b9 Germany (DE) 0c24a0f5-7cd3-4455-a0ad-ba79931cfea France (FR) 60dc0153-dd00-4f40-8e31-f7ecdbb24e1d Netherlands (NL) ea1efb97-1a87-47e2-bf08-dc600504b2a3 Spain (ES) 091c08a1-8479-41dd-b9bd-d6bef75fa10d Netherlands (NL) 8a940e67-73b4-49bb-891c-833065fc4952 Poland (PL) 54d343ad-284b-410f-ac9d-cf1092249324 Norway (NO) caac0c8f-6a68-47f9-bd16-6d765ed31fa5 Finland (FI) aa8eaabb-ab1a-49c4-9c01-3de17195f8f6 Netherlands (NL) f87b85a3-aa7a-4f78-acb3-2544eb3d8310 Germany (DE) bf0d6edc-520f-418a-a347-8d1885f5f663 Denmark (DK) b503dbc1-46ce-4cb7-b252-1931887f4bbc Germany (DE) ef86ee0b-c013-4020-9178-b7e95ff540bb Croatia (HR)

Ordering

Order Code US and Canada	XT3SE3200AFF000XXX
E-Number (Finland)	3641019
EAN	8015644021269
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	105 mm
Product Net Height	150 mm
Product Net Depth / Length	70 mm
Product Net Weight	1.7 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	155 mm
Package Level 1 Height	190 mm
Package Level 1 Depth /	155 mm

Length	
Package Level 1 Gross Weight	1.724 kg
Package Level 1 EAN	8015644021269

Additional Information

Circuit Breaker Type to be Associated	Power Distribution
Connecting Capacity Main Circuit	Busbar 85..192 mm²
Current Type	AC/DC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	240 cycles per hour 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Power Loss	at Rated Operating Conditions per Pole 13.2 W
Product Main Type	SACE Tmax XT
Product Name	Leistungsschalter
Product Type	Automatic Circuit Breaker
Rated Current (I _n)	200 A
Rated Frequency (f)	50 / 60 Hz
Rated Voltage (U _r)	690 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Instantaneous Short-Circuit Current Setting (I _i)	2000 A
Rated Insulation Voltage (U _i)	800 V
Rated Operational Voltage	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(220 V AC) 42.5 kA (230 V AC) 42.5 kA (240 V AC) 42.5 kA (380 V AC) 27 kA (415 V AC) 27 kA (440 V AC) 20 kA (500 V AC) 15 kA (525 V AC) 10 kA (690 V AC) 3 kA (250 V DC) 2 Poles in Series 27 kA (500 V DC) 3 Poles in Series 37.5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 40 kA (500 V AC) 30 kA (525 V AC) 20 kA (690 V AC) 6 kA (250 V DC) 2 Poles in Series 36 kA (500 V DC) 3 Poles in Series 50 kA
Rated Uninterrupted Current (I _u)	250 A
Recommended Screw Driver	Main Circuit M8
Release	TMD
Release Type	TM
Setting Range	140...200 A
Short-Circuit Performance	S

Level	
Standards	IEC
Sub-type	XT3
Terminal Connection Type	Front
Terminal Type	Bolt
Tightening Torque	8 N·m
Version	F
CAD Dimensional Drawing	1SDH001295R0409

Certificates and Declarations

ATEX Certificate	No certification needed
Data Sheet, Technical Information	1SDC210100D0206 1SDC210099D0206
Declaration of Conformity - CE	9AKK106713A5530
GL Certificate	1SDL000163R0094
LR Certificate	1SDL000163R0100
UL Certificate	No certification needed
VDE Certificate	No certification needed
Dimension Diagram	1SDH000720R0100
Mechanical Drawings	1SDH000720R0100
Wiring Diagram	1SDM000068R0001
Instructions and Manuals	1SDH000720R0001

Classifications

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

