

PRODUCT-DETAILS

XT4S 250 Ekip L SIG In=250A 4p F F

XT4S 250 Ekip L SIG In=250A 4p F F



| General Information | |
|-----------------------|--|
| Extended Product Type | XT4S 250 Ekip L SIG In=250A 4p F F |
| Product ID | 1SDA068510R1 |
| EAN | 8015644024161 |
| Catalog Description | XT4S 250 Ekip L SIG In=250A 4p F F |
| Long Description | C.BREAKER TMAX XT4S 250 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LSIG R 250 A |

| ABB EcoSolutions | |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value | |
|---|---|
| Circular Design | Design for Closing Resource Loops - Standard EN45555 - 58.5 % |
| Principles Recyclability Rate | |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| End of Life Instructions | 9AKK108468A2352 |
| Group Waste to Landfill | UL 2799 Zero Waste To Landfill Validation available |

| | |
|-------------------------------------|-----------------|
| Target | |
| Toxic Substances Control Act - TSCA | 9AKK108467A8326 |

Eco Transparency

| | |
|---|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1898 |
|---|-----------------|

Environmental

| | |
|---------------------------|--|
| Environmental Information | 9AKK108467A6707 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

Ordering

| | |
|--------------------------|--------------------|
| Order Code US and Canada | XT4SE4250GFF000XXX |
| EAN | 8015644024161 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 140 mm |
| Product Net Height | 160 mm |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight | 2.939 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 151 mm |
| Package Level 1 Height | 214 mm |
| Package Level 1 Depth / Length | 171 mm |
| Package Level 1 Gross Weight | 3.094 kg |
| Package Level 1 EAN | 8015644024161 |

Additional Information

| | |
|---------------------------------------|-----------------------------------|
| Circuit Breaker Type to be Associated | Power Distribution |
| Connecting Capacity Main Circuit | Busbar 85..200 mm² |
| Current Type | AC |
| Electrical Durability | 120 cycles per hour 8000 cycle |

| | |
|--|--|
| Mechanical Durability | 240 cycles per hour 25000 cycle |
| Number of Poles | 4 |
| Opening Time | CB with SOR 15 ms CB with UVR 15 ms |
| Order Multiple | 1 piece |
| Power Loss | at Rated Operating Conditions per Pole 16.40 W |
| Product Main Type | SACE Tmax XT |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | Automatic Circuit Breaker |
| Rated Current (I_n) | 250 A |
| Rated Frequency (f) | 50/60 Hz |
| Rated Voltage (U_r) | 690 V AC |
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Rated Insulation Voltage (U_i) | 1000 V AC |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short- Circuit Breaking Capacity (I_{cs}) | (220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 36 kA (525 V AC) 25 kA (690 V AC) 12 kA |
| Rated Ultimate Short- Circuit Breaking Capacity (I_{cu}) | (220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 36 kA (525 V AC) 25 kA (690 V AC) 12 kA |
| Rated Uninterrupted Current (I_u) | 250 A |
| Recommended Screw Driver | Main Circuit M8 |
| Release | Ekip LSIG |
| Release Type | EL |
| Short-Circuit Performance Level | S |
| Standards | IEC |
| Sub-type | XT4 |
| Terminal Connection Type | Front |
| Terminal Type | Bolt |
| Tightening Torque | 8 N·m |
| Version | F |
| CAD Dimensional Drawing | 1SDH001295R0677 |

Certificates and Declarations

| | |
|-----------------------|-------------------------|
| ATEX Certificate | No certification needed |
| Data Sheet, Technical | 1SDC210100D0206 |

| | |
|-----------------------------------|------------------------------------|
| Information | 1SDC210099D0206 |
| Declaration of Conformity - CE | 9AKK106713A5529 |
| GL Certificate | 1SDL000163R0095 |
| LR Certificate | 1SDL000163R0100 |
| UL Certificate | No certification needed |
| VDE Certificate | No certification needed |
| Dimension Diagram | 1SDH000722R0100 |
| Mechanical Drawings | 1SDH000722R0100 |
| Wiring Diagram | 1SDM000068R0001 |
| Instructions and Manuals | 1SDH000722R0001 1SDH000721R0506 |

Classifications

| | |
|----------------------------|--|
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| UNSPSC | 39120000 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| eClass | V11.1 : 27370409 |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

