



PRODUCT-DETAILS

FA2C/MS 1600 3p WMP

FA2C/MS 1600 3p WMP



General Information	
Extended Product Type	FA2C/MS 1600 3p WMP
Product ID	1SDA080478R1
EAN	8015644870065
Catalog Description	FA2C/MS 1600 3p WMP
Long Description	MOVING PART FOR C.BREAKER SWITCH-DISCONNECTOR FORMULA AIR FA2C/MS 1600 THREE-POLE

Material Compliance	
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	d7ad3ec9-79c9-4f15-9c88-83a5b02d1d34 Italy (IT)
Simplified SCIP	f4facf6f-636c-4dd0-b120-8ff4d52f0f6a Germany (DE)

acf7fabf-2d77-4ecc-8a08-b59fa012d07f	Netherlands (NL)
61ff2463-8fd1-4519-9cec-370a2af2932c	Poland (PL)
5ef2cd92-0b0d-4d62-a9db-0b3d6d23ee6e	Norway (NO)
ce07fd87-4861-4b59-81cc-6f482208102f	Finland (FI)
5513ffe7-4bca-45c5-ba0b-dbe8ec4c57dc	Netherlands (NL)
cb9b048c-d04a-453e-b4cd-2cb14735f782	Germany (DE)
f989d3d3-f54a-4f8e-8e72-7f0a447e041c	Denmark (DK)
e457a4b8-6649-4f56-a2f2-629ad51612de	Germany (DE)
ffd8ff9c-a12e-4268-9673-b83c58b3519d	Croatia (HR)
1abb5143-1b2a-4e95-9190-8dd2bff51040	Czech Republic (CZ)
9f5ed5b0-4f19-4c08-8d3b-e69447840d71	Poland (PL)
ca0ef351-c63f-47af-929a-9c475d52478b	Netherlands (NL)
83953438-9f6a-4ad1-96bb-001f17ee8ee9	Netherlands (NL)
47673726-bbba-4e73-b666-ca13e8988050	Estonia (EE)
9bb1d65c-00ed-45c7-8749-0c9ae41ba350	Greece (GR)
a1e3327e-4341-4c8c-8391-f2e818355e44	Portugal (PT)
b87b6d91-eb31-44d0-94d8-8b8fd38349f8	Bulgaria (BG)
6e649d65-12be-49b9-a56d-5efca214e811	Sweden (SE)
c3551085-2d1e-44c3-911f-e9586d5fc714	France (FR)
7c65af48-2a79-44ef-bfcc-e500537fccf4	Sweden (SE)
005149bc-3a84-4738-88f3-85a50afeadd7	Poland (PL)
de601101-d7c5-4ae6-b484-76f020247ad6	Germany (DE)
9b41e4eb-d889-4ece-86cc-f8fc3f77ff72	Germany (DE)
9b6b1f79-3157-4e05-b694-938215e2c011	France (FR)
79e37daa-0991-4e31-a16a-678bf2f4e6cb	Netherlands (NL)
e78f581c-affe-4506-a04b-32c03139dc5d	Spain (ES)

Environmental

Environmental Information	9AKK108467A6707
---------------------------	-----------------

Ordering

EAN	8015644870065
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	317 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	49 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	515 mm
Package Level 1 Gross Weight	53 kg
Package Level 1 EAN	8015644870065

Additional Information

Product Main Type	Formula Air
Product Name	Switch-disconnector
Product Type	Switch-disconnector
Version	W

Technical

Current Type	AC
Electrical Durability	30 cycles per hour
Mechanical Durability	60 cycles per hour
Neutral Pole Current ([% I _N])	100 %
Number of Poles	3
Rated Current (I _N)	1600 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 42 kA for 3 s 25 kA
Rated Uninterrupted Current (I _u)	1600 A
Rated Voltage (U _r)	690 V
Short-Circuit Performance Level	C
Standards	IEC
Sub-type	FA2
Terminal Connection Type	Withdrawable Circuit-Breakers

Certificates and Declarations

Data Sheet, Technical Information	1SDC200044D0201
Declaration of Conformity - CE	9AAK10103A1376
Instructions and Manuals	1SDH001600R0002

Classifications

ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27371403

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Formula AIR

