



PRODUCT-DETAILS

KP6-40R

KP6-40R Heavy Duty Pushbutton



| General Information | |
|-----------------------|---|
| Extended Product Type | KP6-40R |
| Product ID | 1SFA616105R4001 |
| EAN | 7320500200469 |
| Catalog Description | KP6-40R Heavy Duty Pushbutton |
| Long Description | <p>The KP6-40R Heavy Duty Pushbutton is: Heavy duty rubber - Red - Non-illuminated - Black Plastic - No contact block</p> <p>This Heavy Duty Pushbutton is part of ABB's modular plastic range, the most versatile range with a high level of flexibility and market-leading electrical ratings. Engineered for total reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts ensure reliable operation without the need for maintenance, increasing uptime. A high degree of protection guarantees reliability in extreme environments. The innovative design simplifies the entire process, from selection to easy and quick, tool-free installation. The perfect solution for every application.</p> |

| Ordering | |
|------------------------|------------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 8536508090 |

| Popular Downloads | |
|----------------------------------|---|
| © 2024 ABB. All rights reserved. | 2024/10/18 Subject to change without notice |

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02__ |
| Instructions and Manuals | 1SFC151011M0201 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 0.043 m |
| Product Net Height | 0.02 m |
| Product Net Depth / Length | 0.043 m |
| Product Net Weight | 0.021 kg |

Technical

| | |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +70 °C Storage -40 ... +85 °C |
| Color | Red |
| Actuator Type | Heavy duty rubber |
| Bezel Material | Black Plastic |
| Illumination | Non-illuminated |
| Function | Momentary |
| Enclosure Type NEMA | Type1 Type3R Type4 Type4X |
| Mechanical Durability | 2 million |

Environmental

| | |
|----------------------|------------------------------|
| Degree of Protection | Front IP66 Terminals IP20 |
|----------------------|------------------------------|

Material Compliance

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2022-006479 |
| RoHS Information | 2CMT2022-006498 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 2CMT2023-006523 |
| WEEE Category | Product Not in WEEE Scope |

Certificates and Declarations

| | |
|----------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMT2015-005453 |
| Declaration of Conformity - UKCA | 2CMT2020-006121 |

Container Information

| | |
|--------------------------------|-------------|
| Package Level 1 Units | bag 1 piece |
| Package Level 1 Width | 0.1 m |
| Package Level 1 Depth / Length | 0.1 m |

| | |
|------------------------------|---------------|
| Package Level 1 Height | 0.02 m |
| Package Level 1 Gross Weight | 0.021 kg |
| Package Level 1 EAN | 7320500200469 |

Classifications

| | |
|------------------------------------|--|
| Object Classification Code | S |
| ETIM 6 | EC000221 - Front element for push button |
| ETIM 7 | EC000221 - Front element for push button |
| ETIM 8 | EC000221 - Front element for push button |
| eClass | V11.0 : 27371210 |
| UNSPSC | 39122216 |
| IDEA Granular Category Code (IGCC) | 5212 >> Push button for distribution board |
| E-Number (Finland) | 2338455 |
| E-Number (Sweden) | 3705053 |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Modular Plastic Range

