



PRODUCT-DETAILS

CE3T-10R-01

CE3T-10R-01 Emergency stop



General Information	
Extended Product Type	CE3T-10R-01
Product ID	1SFA619500R1041
EAN	7320500260692
Catalog Description	CE3T-10R-01 Emergency stop
Long Description	<p>The CE3T-10R-01 Emergency stop is: Compact - Emergency stop - Twist release - Maintained - Mushroom 30mm - Red - Non-illuminated - 1NC - 0 NO - 1 NC - 24 ... 300 V</p> <p>This Emergency stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p>The compact range has a high level of dust and water resistance.</p>

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536508090

Popular Downloads	
Data Sheet, Technical	1SFC151007C02_

Information	
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.034 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Mushroom 30mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Twist release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	0
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V
Rated Operational Current DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _e)	(240 V) 1 A
Power Loss	Maximum 2.5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm ² Flexible with Ferrule 2 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm ² Flexible 1 x 0.5 ...1.5 mm ² Flexible 2 x 0.5 ...1.5 mm ² Solid 1 x 0.5...1.5 mm ² Solid 2 x 0.5...1.5 mm ²
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA	
Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental	
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	c859009c-dc65-4e4d-8006-77b85b56fa30 Sweden (SE)
Simplified SCIP	7e623a76-b0df-4a7a-8cd8-fcb572704b96 Germany (DE) 744766bc-cdd3-4926-975c-e221f3578bbf Estonia (EE) b129f2bd-d958-4c5a-a342-f35c68513bbb Greece (GR) a4e74ad9-a4a9-4318-a2e1-69297224eb96 Hungary (HU) 492f12c0-5763-4bd5-a39e-12c5d5d45d25 Belgium (BE) 1189b362-5866-41e2-a30a-cafd111033a7 Spain (ES) 47d619ea-d2df-4c4f-aab6-b31eda401a57 Germany (DE) ef9cbfef-f7d2-41ea-a453-e81373a16955 Germany (DE) c23bea4d-dbb5-40ca-b975-8028ba56608f Hungary (HU) 598a84a9-5cb4-4951-8c5c-4f2b93d9b97c France (FR) c1414e50-e90d-40b6-8446-efd65c880f5f Poland (PL) ea18b805-ef4e-4110-bf81-a17ab5b08685 Germany (DE) 57072c90-1ef1-4be7-8b26-f321b1167712 Belgium (BE) 3c8f095e-6efb-4182-a469-7882a2ad29c6 Denmark (DK) bc106146-654e-4a7b-9eb0-787794a85b28 Germany (DE) b579237c-502c-4e75-9599-1d7ba7df0c88 Italy (IT) a7dbbc93-fdf9-4f35-9f2b-5e6e3e380e0b Poland (PL) 4421749b-84cd-4a86-98cf-b30f9ecb17ff Croatia (HR) 7db1ba7d-2ff7-4f9f-81e7-34b9efa714e0 Netherlands (NL) c5685138-30dd-4277-b3e8-b1768f8be2fe9 Czech Republic (CZ) 13cbfdf3-0049-4ac4-90f6-b1e0699a78cf France (FR) 12b5619e-c930-487b-b347-b304af2a8f3e Poland (PL) d5b9d777-daf5-48ab-a5d5-6d47f81378e4 Sweden (SE) e20a0ffd-65c7-492a-a524-399da46fdd3a Bulgaria (BG) 7ddd3f50-4a06-4e4f-9a19-02d04c6a608b Portugal (PT) b7a527de-58bc-4335-96f0-12899f2dd9d9 Finland (FI) d2cffdae-677a-48c9-8562-0bd958a19ddd Norway (NO)
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	CN54150
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020
cURus Certificate	UL_E496500-20171020

Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006122
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.165 m
Package Level 1 Depth / Length	0.09 m
Package Level 1 Height	0.035 m
Package Level 1 Gross Weight	0.036 kg
Package Level 1 EAN	7320500260692

Classifications

Object Classification Code	S
ETIM 6	EC002034 - Emergency stop complete
ETIM 7	EC002034 - Emergency stop complete
ETIM 8	EC002034 - Emergency stop complete
eClass	V11.0 : 27371244
UNSPSC	39122216
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2313520
E-Number (Norway)	4372730
E-Number (Sweden)	3711500

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CE Compact Emergency Stops and Machine Stops



360°