



PRODUCT-DETAILS

CE3P-10R-02

CE3P-10R-02 Emergency stop



360°

General Information	
Extended Product Type	CE3P-10R-02
Product ID	1SFA619501R1051
EAN	7320500260791
Catalog Description	CE3P-10R-02 Emergency stop
Long Description	<p>The CE3P-10R-02 Emergency stop is: Compact - Emergency stop - Pull release - Maintained - Mushroom 30mm - Red - Non-illuminated - 2NC - 0 NO - 2 NC - 24 ... 300 V</p> <p>This Emergency stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p>The compact range has a high level of dust and water resistance.</p>

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536508090

Popular Downloads	
Data Sheet, Technical	1SFC151007C02_

Information

Instructions and Manuals	1SFC151011M0201
--------------------------	-----------------

Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.032 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Mushroom 30mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Pull release
Number of Auxiliary Contacts NC	2
Number of Auxiliary Contacts NO	0
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V
Rated Operational Current DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _e)	(240 V) 1 A
Power Loss	Maximum 5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm ² Flexible with Ferrule 2 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm ² Flexible 1 x 0.5 ...1.5 mm ² Flexible 2 x 0.5 ...1.5 mm ² Solid 1 x 0.5...1.5 mm ² Solid 2 x 0.5...1.5 mm ²
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA	
Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental	
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	ff83c943-3710-4024-be97-c17466175c31 Sweden (SE)
Simplified SCIP	98c5d0b7-e9d2-461f-9cef-869d934f402e Germany (DE) b4fa2ea9-a50c-4b86-a590-1e029d984224 Belgium (BE) 26b9f5c8-a0b5-4d2e-a38b-538da26e9e0a Germany (DE) 8f6c9ca3-9890-44f9-991d-31d601e8bc35 Germany (DE) d22d561f-d879-450b-a457-02bf2375dca7 Hungary (HU) a770fdbf-924b-4968-90da-b3dbab871f89 France (FR) 793e4037-c13d-4e1a-af32-3600506d2509 Spain (ES) 0d5cf7cf-d05e-41d8-81e6-6083d0b22c28 France (FR) 948c6d60-e012-4cbb-806c-4dbd4188a3e0 Poland (PL) 9a82a5a0-5d33-4a57-98a4-06b91110a0e2 Sweden (SE) be5510dc-4c29-4c2c-b75a-c0c24581125a Bulgaria (BG) 25abb10b-0880-4794-94fa-e47642fa2e3d Portugal (PT) 158c3312-6d34-401f-843b-d81f9477c467 Greece (GR) fd66b057-b703-4521-82d8-8572d635a95c Estonia (EE) c67a8f36-01d4-4c75-8971-7dc49a990b7c Netherlands (NL) e73c89fa-92f2-4937-b869-3ef0f9c47864 Hungary (HU) 67353563-b2cf-487b-afa4-380a41fb1cfc Czech Republic (CZ) 31ea8d66-ca8d-414d-8aad-b5e5a4404d98 Poland (PL) e6785d2a-500c-4675-abf5-d20fa861db37 Croatia (HR) 5e6aac0b-52f7-40d2-993c-a2e96ff20a8e Denmark (DK) 85346019-19a0-41d6-8e9e-a69adbac89c9 Germany (DE) e8bdc01e-6938-4e58-9008-e8ddea48c7e9 Belgium (BE) 05f304fd-f0f8-4a64-bf3e-2a1863a10a34 Italy (IT) dc80c424-e990-4524-82b4-e613ddb3f766 Norway (NO) 5c10f0d9-2bbf-4f36-af3c-d07efe009dbf Finland (FI) 87e3c318-37dc-4a36-bd9c-3117d3590201 Germany (DE) d14f00ed-d1c2-425e-8307-648b57263669 Poland (PL)
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	CN54150
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020
cURus Certificate	UL_E496500-20171020

Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006122
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.165 m
Package Level 1 Depth / Length	0.09 m
Package Level 1 Height	0.035 m
Package Level 1 Gross Weight	0.035 kg
Package Level 1 EAN	7320500260791

Classifications

Object Classification Code	S
ETIM 6	EC002034 - Emergency stop complete
ETIM 7	EC002034 - Emergency stop complete
ETIM 8	EC002034 - Emergency stop complete
eClass	V11.0 : 27371244
UNSPSC	39122216
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2313528
E-Number (Norway)	4372746
E-Number (Sweden)	3711506

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CE Compact Emergency Stops and Machine Stops

