



PRODUCT-DETAILS

# CE4T-10R-11

## CE4T-10R-11 Emergency stop



General Information	
Extended Product Type	CE4T-10R-11
Product ID	1SFA619550R1071
EAN	7320500260838
Catalog Description	CE4T-10R-11 Emergency stop
Long Description	The CE4T-10R-11 Emergency stop is: Compact - Emergency stop - Twist release - Maintained - Mushroom 40 mm - Red - Non-illuminated - 1NO+1NC - 1 NO - 1 NC - 24 ... 300 V
	This Emergency stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. The compact range has a high level of dust and water resistance.

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536508090

### Popular Downloads

Data Sheet, Technical Information	1SFC151007C02__
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.04 m
Product Net Height	0.04 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.038 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Mushroom 40 mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Twist release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U <sub>i</sub> )	300 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V
Rated Operational Current DC-13 (I <sub>e</sub> )	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I <sub>e</sub> )	(240 V) 1 A
Power Loss	Maximum 5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm <sup>2</sup> Flexible with Ferrule 2 x 0.5...1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1 x 0.5...1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2 x 0.5...1.5 mm <sup>2</sup> Flexible 1 x 0.5 ...1.5 mm <sup>2</sup> Flexible 2 x 0.5 ...1.5 mm <sup>2</sup> Solid 1 x 0.5...1.5 mm <sup>2</sup> Solid 2 x 0.5...1.5 mm <sup>2</sup>
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m

Wire Stripping Length

6 mm

Technical UL/CSA	
Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental	
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	d0bd167e-a9df-4f6e-ae0d-ff639f5baa4d Sweden (SE)
Simplified SCIP	7f3a98ac-05db-40bf-8488-a6dbf70b9765 Germany (DE) 119c4b85-db2a-4409-87c4-fea5726b047c Belgium (BE) ae2603dc-1e34-4118-a117-832a508a28a1 Spain (ES) ee2ce854-b0d8-4c51-8da7-5b34bde018e5 Germany (DE) 9569f307-ce44-4cbb-a58f-84376edd2085 France (FR) d54cc484-9d06-4e47-837b-c2f8d55a344e Hungary (HU) b9792a5d-8656-4028-9720-a30697a395d2 Germany (DE) b1e3bafd-1e74-45c2-bdc6-7211f4a035a1 Poland (PL) b1351c09-e4c1-4ed6-922c-7460117506b1 Croatia (HR) 0d0bc485-2f62-497c-aa03-ab190b0867fd Netherlands (NL) babf80ed-d268-441d-8bf0-bc7cf2f4683c Czech Republic (CZ) f633a927-f48e-4ff9-8fb2-204178e7e81b Bulgaria (BG) dc527485-0219-456f-9f40-638e4b554599 Sweden (SE) 10fbaf22-f58c-452b-a0ad-76c57efc4dab Poland (PL) 86408c5d-5779-44e3-a3bb-3b7669539eaf Estonia (EE) d61f775d-7be7-47e1-9bf3-18de1e57b5fd Portugal (PT) f51c996e-263b-44fc-a572-38830148560f Hungary (HU) fa1db5eb-f2df-4013-837f-00203f428e29 Greece (GR) 39507f70-ff04-4e01-8ddc-7b1e623724be France (FR) e78014b6-98fd-4c3e-ad29-9ba12cb7329b Poland (PL) ac6b3a36-d39f-4097-9ddc-de87140d962b Italy (IT) 4f503fbe-bdd5-43ea-9fea-9c154cffe8ea Norway (NO) 2b9a5f54-33a4-412a-abc1-3487bc07756f Finland (FI) 29920415-8b2c-4863-b1e5-8e55462eb568 Germany (DE) 74e3957c-777d-4258-87fe-8d6e60e60d8e Denmark (DK) 26350c65-1d11-4c1e-ba7a-8a74b26ba2f2 Belgium (BE) 99a9cdd4-c8f5-4264-870e-02731e515908 Germany (DE)
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	CN54150
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020

cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006122
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.165 m
Package Level 1 Depth / Length	0.09 m
Package Level 1 Height	0.045 m
Package Level 1 Gross Weight	0.04 kg
Package Level 1 EAN	7320500260838

Classifications

Object Classification Code	S
ETIM 6	EC002034 - Emergency stop complete
ETIM 7	EC002034 - Emergency stop complete
ETIM 8	EC002034 - Emergency stop complete
eClass	V11.0 : 27371244
UNSPSC	39122216
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2313542
E-Number (Norway)	4372760
E-Number (Sweden)	3711520

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CE Compact Emergency Stops and Machine Stops

Medium Voltage Products and Systems → Service → Spares and Consumables → Parts → All Spare Parts (Relays-SWG-CB)

