



PRODUCT-DETAILS

CE4P-10R-11

CE4P-10R-11 Emergency stop



360°

General Information	
Extended Product Type	CE4P-10R-11
Product ID	1SFA619551R1071
EAN	7320500260869
Catalog Description	CE4P-10R-11 Emergency stop
Long Description	<p>The CE4P-10R-11 Emergency stop is: Compact - Emergency stop - Pull release - Maintained - Mushroom 40 mm - Red - Non-illuminated - 1NO+1NC - 1 NO - 1 NC - 24 ... 300 V</p> <p>This Emergency stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p>The compact range has a high level of dust and water resistance.</p>

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536508090

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02__
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.04 m
Product Net Height	0.04 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.038 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Red
Actuator Type	Mushroom 40 mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Pull release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V
Rated Operational Current DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _e)	(240 V) 1 A
Power Loss	Maximum 5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm ² Flexible with Ferrule 2 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm ² Flexible 1 x 0.5 ...1.5 mm ² Flexible 2 x 0.5 ...1.5 mm ² Solid 1 x 0.5...1.5 mm ² Solid 2 x 0.5...1.5 mm ²
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m

Wire Stripping Length

6 mm

Technical UL/CSA	
Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental	
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	2dac81d1-2d94-4dcd-8f3f-0f0e786c1067 Sweden (SE)
Simplified SCIP	91593f33-dab9-4ec8-b5df-d307612f49d2 Germany (DE) 781a7d2c-acac-40c3-aeca-a231ca2e16fc Italy (IT) 6915b021-17c1-4079-b034-b425ed38e57f Estonia (EE) 454f3bea-67d0-4240-94d8-1d3f00b21f72 Portugal (PT) 614f6cd3-abee-40f9-9d1b-b7b39de2dd1b Bulgaria (BG) 77cb45c6-faea-441f-b2bb-844599f6a751 Sweden (SE) 772b9489-c11a-48c2-b549-4ece3a229ecb Spain (ES) 4cfa86d7-170a-4874-9d16-954634fad45e Belgium (BE) 10cc3508-a105-4af1-bd02-7f20712bb50d Hungary (HU) 91513d51-2f05-4202-b009-901fbd9ec329 Poland (PL) ed210ff0-0ba0-4bf4-a812-87e363a5c238 France (FR) 2c1bf1d3-f361-4984-ad87-f128335073f8 Germany (DE) 2003098f-9255-402a-ad7c-a1e050268be6 Germany (DE) 9ea13a47-2ab6-4c0f-a01d-e95ec3e1f107 France (FR) 1cfa2e38-96df-4c4e-aacf-49008587df65 Croatia (HR) b8cd9f4d-1356-4de7-95cd-eddeee552fc0 Poland (PL) d1549a8b-d792-4826-abd2-86df57029c68 Czech Republic (CZ) 0de4672d-8a0e-4961-a994-63da623a9cee Netherlands (NL) 4a6e15c8-d475-4d92-8262-5e05a8c5a371 Hungary (HU) ba32b31d-81a8-4266-97f4-9cec02608f52 Greece (GR) f8a475f1-3212-4c61-9339-cfe0fb2f03cb Poland (PL) 7a7f71b5-47f2-4ee6-8f87-aa7b29a7f18d Norway (NO) fc3b271c-e3ed-41b6-a827-9492cc086c53 Finland (FI) fce1cf1b-49e3-4502-910b-add15266c813 Belgium (BE) e4163f38-69f0-4211-80bc-75cac312f102 Germany (DE) 3246b63d-93fc-4b8a-8f66-a9cbc675497c Denmark (DK) 6cd2b4b2-e411-412b-ab1f-8b0b796581d3 Germany (DE)
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	CN54150
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020

cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006122
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.165 m
Package Level 1 Depth / Length	0.09 m
Package Level 1 Height	0.045 m
Package Level 1 Gross Weight	0.04 kg
Package Level 1 EAN	7320500260869

Classifications

Object Classification Code	S
ETIM 6	EC002034 - Emergency stop complete
ETIM 7	EC002034 - Emergency stop complete
ETIM 8	EC002034 - Emergency stop complete
eClass	V11.0 : 27371244
UNSPSC	39122216
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2313546
E-Number (Norway)	4372815
E-Number (Sweden)	3711524

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CE Compact Emergency Stops and Machine Stops

