

[Home](#) > [Electrification](#) > [Automation & Control](#) > [Contactors](#) > [Contactors >= 100A](#) > UA110-30-11 24V 50Hz /

ABB

Genuine products

Dedicated
Support

Doorstep Delivery

eMart

Share with your friends



Automation & Control

UA110-30-11 24V 50Hz / 24V 60Hz Contactor

Out of stock

Upon Request

Product Id#: 1SFL451022R8111

[Be the first to review this product](#)

A 3-phase Contactor suitable for Capacitor switching application. Maximum permissible peak current 30 times the nominal RMS current. Operated with a control voltage, versions from 24V to 690 V

Enquire Now



More about UA110-30-11 24V 50Hz / 24V 60Hz Contactor

Technical Specification

MRP (Indian Rupees)	Not for Retail Sale
Number of Main Contacts NO	3
Compatibility	Capacitor Duty Contactors
Mounted Aux Contacts	1 NO, 1 NC
Max Mechanical Switching Frequency	3600 cycles per hour
Max Electrical Switching Frequency	240 cycles per hour
Conventional Free-air Thermal Current (Ith)	acc. to IEC 60947-4-1, Open Contactors q = 40
Coil Consumption	Holding at Max. Rated Control Circuit Voltage Holding at Max. Rated Control Circuit Voltage Pull-in at Max. Rated Control Circuit Voltage 50 Hz Pull-in at Max. Rated Control Circuit Voltage 60 Hz
Terminal Type	Cable Clamp
Rated Operational Voltage	Main Circuit 1000 volt
Operate Time	Between Coil De-energization and NC Contact ... 18 millisecond, Between Coil Energization and NC Contact ... 22 millisecond, Between Coil Energization and NO Contact
Rated Control Circuit Voltage (Uc)	50 Hz 24V; 60 Hz 24V
Rated Operational Power AC-6b (Pe)	(230 / 240 V) 40 °C, 50 / 60 Hz 40 KVR, (230 / 400 V) 70 °C, 50 / 60 Hz 35 KVR / 60 Hz 75 KVR, (400 / 415 V) 70 °C, 50 / 60 Hz 70 KVR, (440 V) 40 °C,
Rated Frequency Limits	25 ... 400 hertz
Rated Frequency (f)	Main Circuit 50/60 hertz
Number of Aux Contacts NO	1

Enquire Now



Rated Short-time Withstand Current (Icw)	at 40 °C Ambient Temp, in Free Air, from a Col at 40 °C Ambient Temp, in Free Air, from a Col ampere, at 40 °C Ambient Temp, in Free Air, fr 350 ampere, at 40 °C Ambient Temp, in Free A
Max Operating Voltage UL/CSA	Main Circuit 600 volt
Package Width	130 millimetre
Package Length	265 millimetre
Package Height	162 millimetre
Invoice Description	UA110-30-11 24V 50Hz / 24V 60Hz Contactor
Product Range	Capacitor Duty Contactors
Package Gross Weight	2 kilogram
Extended Product Type	UA110-30-11-81
Number of Aux Contacts NC	1
Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 deg Contactor Fitted with Thermal O/L Relay (0.85 degree Celsius, Close to Contactor without Tr 1.1 Uc) -40 ... +70 degree Celsius
Rated Insulation Voltage (Ui)	acc. to UL/CSA 600 volt, acc. to IEC 60947-4-1 1000 volt
Product Class	Block Contactors
Total GST Percentage	18.00
HSN Number	85364900
Country of origin	Sweden (SE) - Imported by ABB India Limited

[Download](#)

[Reviews](#)

Recently Viewed




 <p><u>MLBL-04YN LED block</u> 1SIN611621R1043 ₹116.58</p>	 <p><u>A9-30-01 400-415V 50Hz / 415-440V 60Hz Contactor</u> 1SBL141001R8601 ₹827.06</p>	 <p><u>A9-30-10 110V 50Hz / 110-120V 60Hz Contactor</u> 1SBL141001R8410 ₹673.19</p>	<u>A9-</u>
---	---	---	------------


Write to Us


1800 420 0707


@ contactabb.in@abb.com
(Only for India Inquiries)

Disha - Plot No.5 & 6, 2nd Stage, Peenya
Industrial Area IV, Peenya 560058,
Bangalore, Karnataka, India.

Facebook

Twitter

Linkedin

Youtube

COMPANY

INFORMATION

About Us

Sell With Us

Our Sellers

Blogs

Exchange and Returns Policy

Privacy Policy

Terms of Use

How to create a Company Account

FAQ

Enquire Now

Copyright © 2025 ABB India Ltd. | Address: Disha - Plot No.5 & 6, 2nd Stage, Peenya Industrial Area IV, Peenya 560058, Bang

https://shop.in.abb.com/1sfl451022r8111/ua110-30-11-24v-50hz-24v-60hz-contactor.html?srsftid=AfmBOopJZ3V5u1Fh8FLXHIISQ8VAQgMFE5xCaku...

4/4