



PRODUCT-DETAILS

UA110-30-11-86

UA110-30-11 400-415V 50Hz / 415-440V 60Hz  
Contactor



General Information	
Extended Product Type	UA110-30-11-86
Product ID	1SFL451022R8611
EAN	7320500189276
Catalog Description	UA110-30-11 400-415V 50Hz / 415-440V 60Hz Contactor
Long Description	A 3-phase Contactor suitable for Capacitor switching application. Maximum permissible peak current 30 times the nominal RMS current. Operated with a control voltage, versions from 24V to 690 V

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	1SBC101145L0202
Instructions and	5309660-60

Manuals

CAD Dimensional Drawing	2CDC001079B0201
-------------------------	-----------------

Dimensions

Product Net Width	102 mm
Product Net Depth / Length	123.5 mm
Product Net Height	148 mm
Product Net Weight	1.8 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I <sub>th</sub> )	acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 160 A
Rated Operational Power AC-6b (P <sub>e</sub> )	(230 / 240 V) 40 °C, 50 / 60 Hz 40 kvar (230 / 240 V) 55 °C, 50 / 60 Hz 40 kvar (230 / 240 V) 70 °C, 50 / 60 Hz 35 kvar (400 / 415 V) 40 °C, 50 / 60 Hz 75 kvar (400 / 415 V) 70 °C, 50 / 60 Hz 65 kvar (400 / 415 V) 55 °C, 50 / 60 Hz 70 kvar (440 V) 40 °C, 50 / 60 Hz 75 kvar (440 V) 55 °C, 50 / 60 Hz 75 kvar (440 V) 70 °C, 50 / 60 Hz 70 kvar (500 / 550 V), 40 °C, 50 / 60 Hz 80 kvar (500 / 550 V) 55 °C, 50 / 60 Hz 80 kvar (500 / 550 V) 70 °C, 50 / 60 Hz 75 kvar (690 V) 40 °C, 50 / 60 Hz 90 kvar (690 V) 55 °C, 50 / 60 Hz 90 kvar (690 V) 70 °C, 50 / 60 Hz 85 kvar
Rated Short-time Withstand Current Low Voltage (I <sub>cw</sub> )	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 800 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 175 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 350 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1320 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 500 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 440 V 1160 A cos phi=0.45 (cos phi=0.35 for I <sub>e</sub> > 100 A) at 690 V 800 A
Maximum Electrical Switching Frequency	240 cycles per hour
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Main Circuit 8 kV
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U <sub>c</sub> Min. ... 1.1 x U <sub>c</sub> Max. (at Θ ≤ 70 °C)
Rated Control Circuit	50 Hz 400 ... 415 V

Voltage (U <sub>c</sub> )	60 Hz 415 ... 440 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 22 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 26 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 350 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 450 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 15 ms Between Coil De-energization and NO Contact Opening 10 ... 18 ms Between Coil Energization and NC Contact Opening 7 ... 22 ms Between Coil Energization and NO Contact Closing 10 ... 25 ms
Connecting Capacity Main Circuit	Bar 30 mm <sup>2</sup> Flexible with Cable End 1 x 10 ... 70 mm <sup>2</sup> Rigid 2 x 6 ... 65 mm <sup>2</sup>
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup> Flexible 2x0.75 ... 2.5 mm <sup>2</sup> Solid 2 x 1 ... 4 mm <sup>2</sup> Stranded 2 x 1 .... 4 mm <sup>2</sup>
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M8 hexagon socket screw with single connector
Terminal Type	Cable Clamp

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
-------------------------------------	--------------------

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U <sub>c</sub> ) -25 ... 50 ° C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U <sub>c</sub> ) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: B1 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C1 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C2 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B1 5 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B2 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C1 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C2 20 g

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202

RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	SE-72473
CQC Certificate	CQC2003010304088242 CQC2009010304353513
cULus Certificate	20160916- E36588
Declaration of Conformity - CCC	2020980304001551 2020980304001055
Declaration of Conformity - CE	2CMT2015-005436
Declaration of Conformity - UKCA	2CMT2020-006118

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	130 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	162 mm
Package Level 1 Gross Weight	2 kg
Package Level 1 EAN	7320500189276

Classifications

Object Classification Code	Q
ETIM 4	EC001079 - Capacitor magnet contactor
ETIM 5	EC001079 - Capacitor magnet contactor
ETIM 6	EC001079 - Capacitor contactor
ETIM 7	EC001079 - Capacitor contactor
ETIM 8	EC001079 - Capacitor contactor
eClass	V11.0 : 27371006
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4756 >> Capacitor magnet contactor

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → UA and UA..RA Contactors → UA110

