


PRODUCT-DETAILS

AF265-30-11-14

AF265-30-11-14 Contactor



| General Information | |
|-----------------------|--|
| Extended Product Type | AF265-30-11-14 |
| Product ID | 1SFL547002R1411 |
| EAN | 7320500481219 |
| Catalog Description | AF265-30-11-14 Contactor |
| Long Description | <p>The AF265-30-11-14 is a 3 pole - 1000 V IEC or 600 V UL contactor with pre-mounted auxiliary contacts and Main Circuit Bars, controlling motors up to 132 kW / 400 V AC (AC-3) or 200 hp / 480 V UL and switching power circuits up to 400 A (AC-1) or 350 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (250-500 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p> |

| Ordering | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

| Popular Downloads | |
|-----------------------|-----------------|
| Data Sheet, Technical | 1SBC100192C0206 |

Information

| | |
|--------------------------|-----------------|
| Instructions and Manuals | 1SFC100008M0201 |
| CAD Dimensional Drawing | 2CDC001079B0201 |
| Dimension Diagram | 1SFB535001G1060 |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width | 140 mm |
| Product Net Depth / Length | 180 mm |
| Product Net Height | 225 mm |
| Product Net Weight | 3.9 kg |

Technical

| | |
|---|---|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 1 |
| Number of Auxiliary Contacts NC | 1 |
| Rated Operational Voltage | Main Circuit 1000 V |
| Rated Frequency (f) | Main Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current (I_{th}) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 400 A |
| Rated Operational Current AC-1 (I_e) | (1000 V) 40 °C 350 A (1000 V) 55 °C 300 A (1000 V) 60 °C 300 A (1000 V) 70 °C 240 A (690 V) 40 °C 400 A (690 V) 55 °C 350 A (690 V) 70 °C 290 A |
| Rated Operational Current AC-3 (I_e) | (415 V) 55 °C 265 A (440 V) 55 °C 265 A (500 V) 55 °C 250 A (690 V) 55 °C 250 A (1000 V) 55 °C 113 A (380 / 400 V) 55 °C 265 A (220 / 230 / 240 V) 55 °C 265 A |
| Rated Operational Power AC-3 (P_e) | (415 V) 132 kW (440 V) 160 kW (500 V) 160 kW (690 V) 200 kW (1000 V) 160 kW (380 / 400 V) 132 kW (220 / 230 / 240 V) 75 kW |
| Rated Breaking Capacity AC-3 | 8 x I_e AC-3 |
| Rated Making Capacity AC-3 | 10 x I_e AC-3 |
| Short-Circuit Protective Devices | gG Type Fuses 500 A |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2120 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 400 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 865 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 2650 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1224 A |
| Maximum Breaking Capacity | cos phi=0.45 (cos phi=0.35 for $I_e > 100\text{ A}$) at 440 V 3800 A cos phi=0.45 (cos phi=0.35 for $I_e > 100\text{ A}$) at 690 V 3300 A |

| | |
|---|--|
| Maximum Electrical Switching Frequency | (AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour |
| Rated Operational Current DC-1 (I_e) | (110 V) 2 Poles in Series, 40 °C 350 A (220 V) 3 Poles in Series, 40 °C 350 A |
| Rated Operational Current DC-3 (I_e) | (110 V) 2 Poles in Series, 40 °C 350 A (220 V) 3 Poles in Series, 40 °C 350 A |
| Rated Operational Current DC-5 (I_e) | (110 V) 2 Poles in Series, 40 °C 350 A (220 V) 3 Poles in Series, 40 °C 350 A |
| Rated Insulation Voltage (U_i) | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V |
| Rated Impulse Withstand Voltage (U_{imp}) | Main Circuit 8 kV |
| Mechanical Durability | 5 million |
| Maximum Mechanical Switching Frequency | 300 cycles per hour |
| Coil Operating Limits | (acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C) |
| Rated Control Circuit Voltage (U_c) | 50 Hz 250 ... 500 V 60 Hz 250 ... 500 V DC Operation 250 ... 500 V |
| Coil Consumption | Holding at Max. Rated Control Circuit Voltage 50 Hz 20.4 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 20.4 V·A Holding at Max. Rated Control Circuit Voltage DC 4.7 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 550 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 550 V·A Pull-in at Max. Rated Control Circuit Voltage DC 650 W |
| Operate Time | Between Coil De-energization and NO Contact Opening 37 ... 47 ms Between Coil Energization and NO Contact Closing 25 ... 55 ms |
| Connecting Capacity Main Circuit | Flexible 2 x 70 ... 185 mm ² Rigid Al-Cable 1 x 185 ... 240 mm ² Rigid Cu-Cable 1 x 6 ... 300 mm ² |
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 1 x 1 ... 4 mm ² |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00 |
| Terminal Type | Main Circuit: Bars |

Technical UL/CSA

| | |
|----------------------------------|---|
| NEMA Size | 5 |
| Continuous Current Rating NEMA | 270 A |
| Horsepower Rating NEMA | (200 V AC) Three Phase 75 Hp (230 V AC) Three Phase 100 Hp (460 V AC) Three Phase 200 Hp (575 V AC) Three Phase 200 Hp |
| Maximum Operating Voltage UL/CSA | Main Circuit 1000 V |
| General Use Rating UL/CSA | (600 V AC) 350 A |
| Horsepower Rating UL/CSA | (200 V AC) Three Phase 75 hp (208 V AC) Three Phase 75 hp (220 ... 240 V AC) Three Phase 100 hp (440 ... 480 V AC) Three Phase 200 hp (550 ... 600 V AC) Three Phase 250 hp |

Environmental

| | |
|---|--|
| Ambient Air Temperature | Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C |
| Maximum Operating Altitude Permissible | Without Derating 3000 m |

Material Compliance

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2021-006202 |
| RoHS Information | 2CMT2021-006277 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 2CMT2023-006525 |
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Circular Value

| | |
|--|---|
| ABB EcoSolutions | Yes |
| Circular Design Principles Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 76.3 % |
| End of Life Instructions | 1SFC100104D0201 |
| Group Waste to Landfill Target | Non-hazardous waste is sent to a landfill, where there is no alternative option available within 100km of a facility |
| Improved Resource Efficiency for Customers | Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line |
| Sustainable Material Content | Recycled Metal - 33 % |

Eco Transparency

| | |
|--|-----------------|
| Environmental Product Declaration - EPD | 1SFC100104D0201 |
|--|-----------------|

Certificates and Declarations

| | |
|-------------------------------------|--|
| ABS Certificate | 14-LD1092198-PDA |
| BV Certificate | BV_36353_A0BV |
| CB Certificate | SE-89316 |
| CCS Certificate | GB14T00030 |
| CQC Certificate | CQC2014010304676670 CQC2014010304673866 |
| Declaration of Conformity - CCC | 2020980304001305 2020980304001068 |
| Declaration of Conformity - CE | 2CMT2015-005439 |
| Declaration of Conformity - UKCA | 2CMT2020-006118 |
| DNV Certificate | DNV_E-14043 |
| EAC Certificate | 9AKK107046A8618 |
| GL Certificate | GL_95073-14HH |

| | |
|------------------|-------------------|
| LR Certificate | LR_14_70011(E1) |
| PRS Certificate | TE_2092_880423_16 |
| RINA Certificate | ELE060313XG_002 |
| RMRS Certificate | 9AKK107045A6978 |
| UL Certificate | 20121217-E36588 |
| UL Listing Card | UL_E36588 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 263 mm |
| Package Level 1 Depth / Length | 203 mm |
| Package Level 1 Height | 289 mm |
| Package Level 1 Gross Weight | 4.6 kg |
| Package Level 1 EAN | 7320500481219 |

Classifications

| | |
|------------------------------------|---|
| Object Classification Code | Q |
| ETIM 4 | EC000066 - Magnet contactor, AC-switching |
| ETIM 5 | EC000066 - Magnet contactor, AC-switching |
| ETIM 6 | EC000066 - Power contactor, AC switching |
| ETIM 7 | EC000066 - Power contactor, AC switching |
| ETIM 8 | EC000066 - Power contactor, AC switching |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |
| IDEA Granular Category Code (IGCC) | 4758 >> lec Contactors |
| E-Number (Finland) | 3706477 |
| E-Number (Norway) | 4117649 |
| E-Number (Sweden) | 3210156 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF265

