


PRODUCT-DETAILS

# AF370-40-00-11

## AF370-40-00-11 Contactor



| General Information   |   |
|-----------------------|---|
| Extended Product Type | AF370-40-00-11  |
| Product ID            | 1SFL607102R1100   |
| EAN                   | 7320500504321   |
| Catalog Description   | AF370-40-00-11 Contactor  |
| Long Description      | The AF370-40-00-11 is a 4 pole - 1000 V IEC or 600 V UL contactor with Main Circuit Bars, controlling motors up to 200 kW / 400 V AC (AC-3) / and switching power circuits up to 525 A (AC-1) or 420 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories. |

| Ordering               |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

| Popular Downloads                 |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100192C0206 |

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SFC100008M0201 |
| CAD Dimensional Drawing  | 2CDC001079B0201 |
| Dimension Diagram        | 1SFB535001G1123 |

## Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 184 mm |
| Product Net Depth / Length | 180 mm |
| Product Net Height         | 225 mm |
| Product Net Weight         | 5.7 kg |

## Technical

|   |  |
|---|--|
| Number of Main Contacts NO                                  | 4  |
| Number of Main Contacts NC                                  | 0  |
| Number of Auxiliary Contacts NO                             | 0  |
| Number of Auxiliary Contacts NC                             | 0  |
| Rated Operational Voltage                                   | Main Circuit 1000 V  |
| Rated Frequency (f)   | Main Circuit 60 Hz   |
| Conventional Free-air Thermal Current ( $I_{th}$ )          | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 525 A   |
| Rated Operational Current AC-1 ( $I_e$ )                    | (1000 V) 40 °C 400 A<br>(1000 V) 60 °C 350 A<br>(1000 V) 70 °C 290 A<br>(690 V) 40 °C 525 A<br>(690 V) 60 °C 425 A<br>(690 V) 70 °C 350 A  |
| Rated Operational Current AC-3 ( $I_e$ )                    | (415 V) 55 °C 370 A<br>(440 V) 55 °C 370 A<br>(380 / 400 V) 55 °C 370 A<br>(220 / 230 / 240 V) 55 °C 370 A   |
| Rated Operational Power AC-3 ( $P_e$ )                      | (415 V) 200 kW<br>(440 V) 200 kW<br>(380 / 400 V) 200 kW<br>(220 / 230 / 240 V) 110 kW   |
| Rated Breaking Capacity AC-3                                | 8 x $I_e$ AC-3   |
| Rated Making Capacity AC-3                                  | 10 x $I_e$ AC-3  |
| Short-Circuit Protective Devices                            | gG Type Fuses 630 A  |
| Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ ) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2960 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 600 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 1208 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 3700 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1709 A |
| Maximum Breaking Capacity                                   | $\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100\text{ A}$ ) at 440 V 5000 A   |
| Maximum Electrical Switching Frequency                      | (AC-1) 300 cycles per hour   |
| Rated Insulation Voltage ( $U_i$ )                          | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V<br>acc. to UL/CSA 600 V  |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | Main Circuit 8 kV  |

|   |  |
|---|--|
| Mechanical Durability                   | 5 million  |
| Maximum Mechanical Switching Frequency  | 300 cycles per hour  |
| Coil Operating Limits                   | (acc. to IEC 60947-4-1) 0.85 x Uc Min. ... 1.1 x Uc Max. (at $\theta \leq 70^\circ\text{C}$ )  |
| Rated Control Circuit Voltage ( $U_c$ ) | 50 Hz 24 ... 60 V<br>60 Hz 24 ... 60 V<br>DC Operation 20 ... 60 V   |
| Coil Consumption                        | Holding at Max. Rated Control Circuit Voltage 50 Hz 8.5 V·A<br>Holding at Max. Rated Control Circuit Voltage 60 Hz 8.5 V·A<br>Holding at Max. Rated Control Circuit Voltage DC 3 W<br>Pull-in at Max. Rated Control Circuit Voltage 50 Hz 475 V·A<br>Pull-in at Max. Rated Control Circuit Voltage 60 Hz 475 V·A<br>Pull-in at Max. Rated Control Circuit Voltage DC 400 W |
| Operate Time                            | Between Coil De-energization and NO Contact Opening 45 ... 80 ms<br>Between Coil Energization and NO Contact Closing 30 ... 60 ms  |
| Connecting Capacity Main Circuit        | Flexible 1 x 16 ... 240 mm <sup>2</sup><br>Rigid Al-Cable 1 x 185 ... 240 mm <sup>2</sup><br>Rigid Cu-Cable 2 x 70 ... 185 mm <sup>2</sup>   |
| Connecting Capacity Auxiliary Circuit   | Flexible with Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible 2x0.75 ... 2.5 mm <sup>2</sup><br>Solid 2 x 1 ... 4 mm <sup>2</sup><br>Stranded 2 x 1 ... 4 mm <sup>2</sup>   |
| Degree of Protection                    | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00   |
| Terminal Type                           | Main Circuit: Bars   |

## Technical UL/CSA

|                                  |   |
|----------------------------------|---|
| Maximum Operating Voltage UL/CSA | Main Circuit 1000 V   |
| General Use Rating UL/CSA        | (600 V AC) 420 A  |
| Horsepower Rating UL/CSA         | (200 ... 208 V AC) Three Phase 50 Hp<br>(200 V AC) Three Phase 125 hp<br>(208 V AC) Three Phase 125 hp<br>(220 ... 240 V AC) Three Phase 60 Hp<br>(220 ... 240 V AC) Three Phase 150 hp<br>(440 ... 480 V AC) Three Phase 125 Hp<br>(440 ... 480 V AC) Three Phase 300 hp<br>(550 ... 600 V AC) Three Phase 150 Hp<br>(550 ... 600 V AC) Three Phase 350 Hp |

## Environmental

|  |  |
|--|--|
| Ambient Air Temperature                | Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C<br>Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C<br>Close to Contactor for Storage -40 ... 70 °C |
| Maximum Operating Altitude Permissible | Without Derating 3000 m  |

## Material Compliance

|   |  |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658  |
| REACH Declaration                           | 2CMT2021-006202  |
| RoHS Information                            | 2CMT2021-006277  |
| RoHS Status                                 | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA         | 2CMT2023-006525  |

WEEE B2C / B2B

Business To Business

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

## Circular Value

|  |   |
|--|---|
| ABB EcoSolutions                                 | Yes   |
| Circular Design Principles<br>Recyclability Rate | Design for Closing Resource Loops - Standard EN45555 - 76.3 %   |
| End of Life Instructions                         | 1SFC100104D0201   |
| Group Waste to Landfill<br>Target                | Non-hazardous waste is sent to a landfill, where there is no alternative option<br>available within 100km of a facility                     |
| Improved Resource<br>Efficiency for Customers    | Product Efficiency - Product considered more energy-efficient compared to<br>similar product on market or older products from the same line |
| Sustainable Material<br>Content                  | Recycled Metal - 33 %   |

## Eco Transparency

|  |                 |
|--|-----------------|
| Environmental Product<br>Declaration - EPD | 1SFC100104D0201 |
|--|-----------------|

## Certificates and Declarations

|                                     |                     |
|-------------------------------------|---------------------|
| ABS Certificate                     | 14-LD1092198-PDA    |
| BV Certificate                      | BV_36353_A0BV       |
| CB Certificate                      | SE-89316            |
| CQC Certificate                     | CQC2014010304676670 |
| Declaration of Conformity<br>- CCC  | 2020980304001305    |
| Declaration of Conformity<br>- CE   | 2CMT2015-005439     |
| Declaration of Conformity<br>- UKCA | 2CMT2020-006118     |
| EAC Certificate                     | 9AKK107046A8618     |
| LR Certificate                      | LR_14_70011(E1)     |
| PRS Certificate                     | TE_2092_880423_16   |
| RINA Certificate                    | ELE060313XG_002     |
| RMRS Certificate                    | 9AKK107045A6978     |
| UL Certificate                      | 20140910-E73397     |

## Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 212 mm        |
| Package Level 1 Depth /<br>Length | 262 mm        |
| Package Level 1 Height            | 212 mm        |
| Package Level 1 Gross<br>Weight   | 6.4 kg        |
| Package Level 1 EAN               | 7320500504321 |

| Classifications                    |   |   |
|------------------------------------|---|---|
| Object Classification Code         |   | Q |
| ETIM 4                             | EC000066 - Magnet contactor, AC-switching |   |
| ETIM 5                             | EC000066 - Magnet contactor, AC-switching |   |
| ETIM 6                             | EC000066 - Power contactor, AC switching  |   |
| ETIM 7                             | EC000066 - Power contactor, AC switching  |   |
| ETIM 8                             | EC000066 - Power contactor, AC switching  |   |
| eClass                             | V11.0 : 27371003                          |   |
| UNSPSC                             | 39121529                                  |   |
| IDEA Granular Category Code (IGCC) | 4758 >> Iec Contactors                    |   |
| E-Number (Finland)                 | 3707243                                   |   |

| Categories  |
|---|
| Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF370 |

