

PRODUCT-DETAILS

OT16F4C

OT16F4C CHANGE-OVER SWITCH



General Information

Extended Product Type	OT16F4C
Product ID	1SCA104831R1001
EAN	6417019389752
Catalog Description	OT16F4C CHANGE-OVER SWITCH
Long Description	16A Manual Change-Over Switch, Handle and shaft need to be ordered separately, Open transition

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads		
Data Sheet, Technical Information		1SCC303003C0201
Instructions and Manuals		1SCC301054M0006
Dimensions		
Product Net Width		96 mm 3.78 in
Product Net Height		68 mm 2.68 in
Product Net Depth / Length		68 mm 2.68 in
Product Net Weight		0.31 kg 0.68 lb
Technical		
Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 16 A	
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 16 A	
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 10 A	
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 7.5 kW (500 V) 7.5 kW (690 V) 7.5 kW	
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40\text{ }^{\circ}\text{C}$ 25 A	
Conventional Thermal Current (I_{the})	Fully Enclosed 25 A	
Rated Impulse Withstand Voltage (U_{imp})		8 kV
Rated Insulation Voltage (U_i)		750 V
Rated Operational Voltage		750 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 0.5 kiloampere rms	
Power Loss		0.3 W
Pollution Degree		3
Handle Color		Black
Handle Type	Handle and shaft not included	
Fourth Pole Position		Right Side
Fourth Pole Type	Switched - Simultaneous Function	
Switches Operating Mechanism	Mechanism on Top of the Switch	
Distance Between Phases		Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out	
Operating Mode		Front operated
Standards		UL 98 / IEC60947-3

Mounting Type	Base mounting
Number of Poles	4
Cable Cross-Section	0.75 ... 10 mm²
Degree of Protection	Front IP20
Transition Type	Open

Technical UL/CSA

Ampere Rating	16 A
Horsepower Rating UL/CSA	(acc. to UL 200 V) 3 Hp (acc. to UL 208 V) 3 Hp (acc. to UL 240 V) 5 Hp (acc. to UL 480 V) 10 Hp (acc. to UL 600 V) 10 Hp

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Certificates and Declarations

Declaration of Conformity - CE	1SCC303019D2702
REACH Declaration	1SCC011021D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	80 mm 3.15 in
Package Level 1 Depth / Length	108 mm 4.25 in
Package Level 1 Height	79 mm 3.11 in
Package Level 1 Gross Weight	0.31 kg 0.68 lb
Package Level 1 EAN	6417019389752

Classifications

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5290 >> Disconnect switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601423

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

