

PRODUCT-DETAILS

# OTM63F3C20D400C

## OTM63F3C20D400C AUTOMATIC TRANSFER SWITCH



### General Information

Extended Product Type	OTM63F3C20D400C
Product ID	1SCA151423R1001
EAN	6417019818283
Catalog Description	OTM63F3C20D400C AUTOMATIC TRANSFER SWITCH
Long Description	Automatic transfer switch, motor operated, open transition type 1-0-2. Self-supplied unit with fixed operating parameters.

### Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

### Ordering

Customs Tariff Number	85365080
Country of Origin	China (CN)

Popular Downloads	
Data Sheet, Technical Information	1SCC308001B0201
Instructions and Manuals	2THT303803P4001
Mechanical Drawings	OTM63-125_2P_3P_COMPACTATS

Dimensions	
Product Net Height	103 mm
Product Net Depth / Length	131 mm
Product Net Weight	1.75 kg

Technical	
Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 63 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 63 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 63 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 63 A
Rated Operational Current AC-32B ( $I_e$ )	(380 ... 415 V) 63 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 63 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 30 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$\Theta = 40\text{ }^{\circ}\text{C}$ 63 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	800 V
Rated Operational Voltage	380...415 V AC
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 2.5 kiloampere rms
Motor Operational Voltage	380...415 V AC
Power Loss	2.8 W
Pollution Degree	3
Handle Type	Direct mounted handle
Fourth Pole Type	Switched - Simultaneous Function
Position of Line Terminals	Supplies on Top - Load on Bottom
Controller Type	20D
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Open

Environmental	
---------------	--

Certificates and Declarations

Declaration of Conformity - CE	No declaration needed
REACH Declaration	1SCC011021D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	103 mm
Package Level 1 Depth / Length	275 mm
Package Level 1 Height	168 mm
Package Level 1 Gross Weight	1.95 kg

Classifications

ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
UNSPSC	39122214
IDEA Granular Category Code (IGCC)	5208 >> Controller switch
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3640445

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Compact ATS

