

PRODUCT-DETAILS

SB204M-C4 SB204M-C4 Miniature Circuit Breaker - 4P - C -4 A



General Information	
Extended Product Type	SB204M-C4
Product ID	1SYS274012R0044
Catalog Description	SB204M-C4 Miniature Circuit Breaker - 4P - C - 4 A
Long Description	System pro M compact SB200M Miniature Circuit Breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 10 kA at 240/415 V AC) and rated currents (up to 63A). All MCBs of the product range SB200M comply with IS/IEC 60898-1, allowing the use for residential, commercial and industrial applications.

Technical	
Standards	IS/IEC 60898-1
Tripping Characteristic	C
Rated Voltage (U _r)	415 V
Operational Voltage	Maximum 264 V AC Maximum 60 V DC
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Current (I _n)	4 A

© 2024 ABB. All rights reserved.

2024/06/17

Subject to change without notice

SB204M-C4

Rated Operational Current (I _e)	4 A
Rated Short-Circuit Capacity	10 kA
Rated Service Short- Circuit Breaking Capacity (I _{cs})	7.5 kA
Frequency (f)	50 Hz
Rated Frequency (f)	50 Hz
Energy Limiting Class	
Electrical Endurance	20000AC cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	
Number of Poles	4
Overvoltage Category	
Tightening Torque	2 N·n
Actuator Type	Toggle
Screw Terminal Type	Cage Termina
Actuator Marking	
Actuator Material	Insulation Group II, Black, Sealable
Housing Material	Insulation Group II, RAL 7035
Mounting Position	Any
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Remarks	IP40 in enclosure with cove
Connecting Capacity	rigid: 25 mm [;] ; flexible: 16 mm [;]
Connecting Capacity Material Compliance RoHS Information RoHS Status	; flexible: 16 mm ² 1SYM100001D1015
Material Compliance RoHS Information RoHS Status	; flexible: 16 mm ; flexible: 16 mm 1SYM100001D1015 Following EU Directive 2011/65/EU
Material Compliance RoHS Information RoHS Status RoHS Date Conflict Minerals Reporting Template	; flexible: 16 mm 1SYM100001D101 Following EU Directive 2011/65/EU 4354
Material Compliance RoHS Information	; flexible: 16 mm 1SYM100001D1015 Following EU Directive 2011/65/EL 43546
Material Compliance RoHS Information RoHS Status RoHS Date Conflict Minerals Reporting Template (CMRT) Environmental	; flexible: 16 mm 1SYM100001D1019 Following EU Directive 2011/65/EL 43540 9AKK108468A3363
Material Compliance RoHS Information RoHS Status RoHS Date Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Reference Ambient Air	; flexible: 16 mm 1SYM100001D1015 Following EU Directive 2011/65/EL 43546 9AKK108468A3363
Material Compliance RoHS Information RoHS Status RoHS Date Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Reference Ambient Air Temperature	: flexible: 16 mm 1SYM100001D1015 Following EU Directive 2011/65/EL 43546 9AKK108468A3363 9AKK108468A3363 0peration -25 +55 °C Storage -40 +70 °C
Material Compliance RoHS Information RoHS Status RoHS Date Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Reference Ambient Air Temperature Degree of Protection	: flexible: 16 mm 1SYM100001D1019 Following EU Directive 2011/65/EU 4354(9AKK108468A3363 9AKK108468A3363 0peration -25 +55 °C Storage -40 +70 °C 30 °C
Material Compliance RoHS Information RoHS Status RoHS Date Conflict Minerals Reporting Template (CMRT) Environmental Ambient Air Temperature Reference Ambient Air Temperature Degree of Protection Pollution Degree	: flexible: 16 mm 1SYM100001D1019 Following EU Directive 2011/65/EU 43540 9AKK108468A3363 9AKK108468A3363 0peration -25 +55 °C Storage -40 +70 °C 30 °C IP20 28 cycle 55°C @ 90-96%
Material Compliance RoHS Information RoHS Status RoHS Date Conflict Minerals Reporting Template (CMRT)	: flexible: 16 mm 1SYM100001D1015 Following EU Directive 2011/65/EL 43546 9AKK108468A3363 9AKK108468A3363 0peration -25 +55 °C Storage -40 +70 °C 30 °C

Dimensions	
Product Net Width	70 mm
Product Net Height	85 mm
Product Net Depth /	69 mm

© 2024 ABB. All rights reserved.

Subject to change without notice

Length	
Product Net Weight	0.47 kg
Built-In Depth (t ₂)	69 mm
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.5 kg
Certificates and Declarations	
Declaration of Conformity - CE	9AKK107492A2248
Installation	
Instructions and Manuals	No document needed
Popular Downloads	
Data Sheet, Technical Information	No document needed
Classifications	
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	Product Not in WEEE Scope
eClass	V11.0 : 27141901
Object Classification Code	F

Categories

 $\label{eq:low-constraint} \text{Low Voltage Products and Systems} \rightarrow \text{Modular DIN Rail Products} \rightarrow \text{Miniature Circuit Breakers MCBs} \rightarrow \text{Miniature Circuit Breakers MCBs}$

SB204M-C4

