



Manual Starter, fractional horsepower, 16A, 2 poles, 1 HP at 277 VAC, toggle operated, red indicator, open style

2510FO2P

Product availability: Stock - Normally stocked in distribution facility

Price*: 135.56 USD

Main

Product	Single Unit Manual Starter		
Туре	F		
Overload Relay Type	Melting alloy		

Complementary

Current Rating	16 A	
cable entry	Without	
Horsepower Rating	1 hp 115 V AC 1 hp 277 V AC 0.75 hp 115 V DC 0.75 hp 230 V DC 2 hp 230 V AC	
Voltage Rating	277 V AC 230 V DC	
Number of Poles	2P	
Control Unit	Toggle switch	
Number of Phases	1 phase	
Pilot Light	Red indicator	
Reset	Manual	
Motor starter type	Non reversing	
Electrical Connection	Screw clamp terminals	
Wire Gauge	AWG 14AWG 12 copper	
Height	4.13 in (104.90 mm)	
Width	1.69 in (42.93 mm)	
Depth	2.22 in (56.39 mm)	

Environment

Product Certifications	UL recognized E42243 CCN NLRV2 CSA LR25490 class 3211 05
NEMA Enclosure Rating	Not rated (onen device)

Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Category	US10CP121101
Discount Schedule	0CP1
GTIN	785901554165
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.52 in (6.4 cm)
Package 1 Width	3.11 in (7.9 cm)
Package 1 Length	4.80 in (12.2 cm)
Package 1 Weight	6.08 oz (172.4 g)

Contractual warranty

Warranty 18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better


Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
PVC free	Yes	

Use Again

○ Repack and remanufacture		
Take-back	No	

Technical Illustration

Dimensions




All dimensions are approximate.
Also see technical drawings and/or documentation.

TI_DIM_2510FO

Technical Illustration

Wiring diagram



REFER TO INSTRUCTION SHEET AND TECHNICAL DOCUMENTATION FOR COMPLETE INFORMATION