



PRODUCT-DETAILS

# SU201M-Z1

## Miniature Circuit Breaker - SU200M - 1P - 1 A - Z



General Information	
Extended Product Type	SU201M-Z1
Product ID	2CDS271337R0218
EAN	4016779932851
Catalog Description	Miniature Circuit Breaker - SU200M - 1P - 1 A - Z
Long Description	SU201M-Z1 Miniature Circuit Breaker Z-Char., 10kA, 1A, 1P UL489

Technical	
Tripping Characteristic	Z
Rated Operational Voltage	acc. to IEC 60898-1 277 V acc. to IEC 60947-2 230 V AC
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV at 2000 m 5 kV at Sea Level 6.2 kV
Dielectric Test Voltage	50/60 Hz-1 min: 2 kV
Input Voltage Type	AC/DC
Rated Current (I <sub>n</sub> )	1 A
Rated Short-Circuit	(230 V AC) 11.2 kA

## Capacity

Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(230 V AC) 15 kA (230 V) 15 kA
---	-----------------------------------

Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(230 V) 15 kA
--	---------------

Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(230 V AC) 11.2 kA
--	--------------------

Rated Frequency (f)	50 / 60 Hz DC
---------------------	------------------

Power Loss	2.4 W at Rated Operating Conditions per Pole 2.4 W
------------	---

Power Supply Connection	Arbitrary
-------------------------	-----------

Contact Position Indication	Red ON / Green OFF
-----------------------------	--------------------

Energy Limiting Class	3
-----------------------	---

Electrical Endurance	20000 AC cycle
----------------------	----------------

Mechanical Endurance	20000 cycle
----------------------	-------------

Number of Protected Poles	1
---------------------------	---

Number of Poles	1P
-----------------	----

Overvoltage Category	III
----------------------	-----

Tightening Torque	2.8 N·m
-------------------	---------

Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
---------------------	--

Actuator Marking	I / O
------------------	-------

Actuator Material	Insulation Group II, Black, Sealable
-------------------	--------------------------------------

Housing Material	Insulation Group I, RAL 7035
------------------	------------------------------

Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
----------------------	--

Mounting Position	any
-------------------	-----

Recommended Screw Driver	Pozidriv 2
--------------------------	------------

Accessories Available	Yes
-----------------------	-----

Connecting Capacity	Busbar 10 / 10 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 25 mm <sup>2</sup> Flexible 0.75 ... 25 mm <sup>2</sup> Flexible 0.75 ... 25 mm <sup>2</sup> Rigid 0.75 ... 35 mm <sup>2</sup> Stranded 0.75 ... 35 mm <sup>2</sup>
---------------------	--

Installation Size	acc. to DIN 43880 3
-------------------	---------------------

Terminal Type	Double Clamp
---------------	--------------

## Material Compliance

RoHS Information	2CDK400595D2705
------------------	-----------------

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

RoHS Date	20200514
-----------	----------

REACH Declaration	9AKK107492A1906
-------------------	-----------------

REACH Information	True - contains substances > 0.1 mass percentage
-------------------	--

REACH Date	20240821
------------	----------

Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
---	-----------------

SCIP	89318623-ff2d-4ce0-aefe-5d16fac11138 Germany (DE)
------	---

## Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
-------------------------	--

Reference Ambient Air Temperature	30 °C
-----------------------------------	-------

Degree of Protection	IP20 IP40 Enclosure with Cover IP40
Pollution Degree	3
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	9AKK107680A9140

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	277 V AC 48 V DC
Interrupting Rating acc. to UL489	(240 V AC) 10 kA (277 V AC) 10 kA (48 V DC) 10 kA
Connecting Capacity UL/CSA	Busbar 18-8 AWG Conductor 18-4 AWG

## Dimensions

Width in Number of Modular Spacings	1.0
Product Net Width	17.5 mm
Product Net Height	111 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.125 kg
Pole Net Weight	0.125 kg
Built-In Depth (t <sub>2</sub> )	69 mm

## Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	0.135 kg

## Certificates and Declarations

Declaration of Conformity - CE	2CDK400595D2705
Declaration of Conformity - UKCA	9AKK108467A5201

## Installation

Instructions and Manuals	2CDC002177D0202
--------------------------	-----------------

## Popular Downloads

Data Sheet, Technical Information	2CDC002177D0202
--------------------------------------	-----------------

External Classifications and Standards				
ETIM 8	EC000042 - Miniature circuit breaker (MCB)			
ETIM 9	EC000042 - Miniature circuit breaker (MCB)			
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)			
WEEE B2C / B2B	Business To Business			
CN8	8536 20 10			
UNSPSC	39121603			
eClass	V11.0 : 27141901			
IDEA Granular Category Code (IGCC)	4899 >> Miniature circuit breaker (MCB) screw-in model			
Standards	CSA 22.2 No. 5 IEC/EN 60947-2 UL 489			
Certification Agency	CSA EN IEC UL			

Accessories				
Identifier	Description	Type	Quantity	Unit Of Measure
2CCA880100R0001	Sensor	CMS-100PS	1	piece
2CCA880101R0001	Sensor	CMS-101PS	1	piece
2CCA880102R0001	Sensor	CMS-102PS	1	piece
2CDS200914R0001	Auxiliary Contact	S2C-H6RU	1	piece
2CDS200924R0001	Signal/Auxiliary Contact	S2C-S6RU	1	piece
2CDS200908R0001	Shunt Trip	S2C-A1U	1	piece
2CDS200908R0002	Shunt Trip	S2C-A2U	1	piece

### Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs → Miniature Circuit Breakers MCBs

