6819/35-24-500 1/4



PRODUCT-DETAILS

## 6819/35-24-500

## Presence Detector Bluetooth 12 m 1380 W DALI studio white matt



**General Information** 

6819/35-24-500 2/4

**Extended Product Type** 6819/35-24-500 Product ID 2CKA006800A2747 EAN 4011395217696 Catalog Description Presence Detector Bluetooth 12 m 1380 W DALI studio white matt Master presence detector with mixed light measurement. For regulating and switching of DALI operating devices that depend on brightness and movement. For DALI broadcast operation (central telegram). Supplies the required voltage for additional DALI operating units and controllers. Suitable for up to 45 DALI operating devices. For changing the colour temperature of >tunable white< lamps, which meet DALI Standard IEC 62386-209 (Device Type 8). Colour temperature can then be set between 2,700 K -6,500 K. With additional switching output for the activation of heating, air conditioning and ventilation or for switching additional loads (e.g. panel light). Configuration possible up to the complete deactivation of the DALI operating devices. With Bluetooth interface for parameterization and operation. Adjustment of all setting Long Description options via smartphone or tablet. Light control via smartphone or tablet app. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With time-controlled basic illumination function. With selectable warm-up function for fluorescent lamps. With 2-step automatic switch-off (according to EnEV / EN 15232). With time-controlled night antiglare function. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor).

| Installation      |               |
|-------------------|---------------|
| Mounting Type     | Built-in      |
| Mounting Position | Ceiling       |
| Mounting Height   | Ontimum 2 4 m |

| Environmental        |                     |
|----------------------|---------------------|
| Ambient Air          | Operation -5 +45 °C |
| Temperature          |                     |
| Degree of Protection | IP40                |

| Technical              |                                    |
|------------------------|------------------------------------|
| Data Sheet, Technical  | 2CKA001673B9577                    |
| Information            |                                    |
| Function               | Setting Options by Bluetooth       |
| Measuring Range        | 12 m                               |
| Number of Outputs      | 1                                  |
| Number of Switching    | 640                                |
| Zones                  |                                    |
| Compatible Bus Systems | DALI                               |
| Transmission Standard  | Bluetooth                          |
| Minimum Switching      | Switch-On 60 second [unit of time] |
| Time                   |                                    |
| Connection Type        | Plug Clamp                         |
| Sensor Type            | Passive infrared                   |
| Illuminance            | 5 2000 lx                          |
| Sensor Detection Range | 360 °                              |
|                        | Horizontal 90 360 °                |

6819/35-24-500 3/4

| Electrical                      |                            |
|---------------------------------|----------------------------|
| Rated Voltage (U <sub>r</sub> ) | 230 V AC                   |
| Auxiliary Voltage AC/DC         | 110 V AC/DC<br>230 V AC/DC |
| Input Voltage Type              | AC                         |
| Current Range                   | Maximum 800 A              |
| Rated Frequency (f)             | 50 / 60 Hz                 |
| Maximum Switching<br>Power      | 1380 W                     |
| Load Type                       | 230 V incandescent lamps   |
| Power Loss                      | 0.3 W                      |

## Design

| Surface Finishing | Untreated<br>Matt   |
|-------------------|---------------------|
| Material          | Thermoplastic       |
| RAL Number        | Similar to RAL 9016 |
| Color             | studio white matt   |

| Dimensions                       |         |
|----------------------------------|---------|
| Product Net Width                | 94 mm   |
| Product Net Height               | 94 mm   |
| Product Net Depth /<br>Length    | 83 mm   |
| Product Net Weight               | 180.8 g |
| Built-In Depth (t <sub>2</sub> ) | 60 mm   |

| Ordering           |         |
|--------------------|---------|
| E-Number (Finland) | 2619390 |
| E-Number (Norway)  | 1471228 |
| E-Number (Sweden)  | 1301059 |

| Material Compliance                               |  |
|---|--|
| RoHS Information                                  | 2CKA200000E6494  |
| RoHS Status                                       | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| REACH Declaration                                 | 2CKA309999E9999  |
| REACH Information                                 | True - contains substances > 0.1 mass percentage                       |
| REACH Date  | 20240705   |
| Conflict Minerals<br>Reporting Template<br>(CMRT) | 9AKK108468A3363  |

| Certificates and Declarations |                 |
|-------------------------------|-----------------|
| Declaration of                | 2CKA200000E6494 |
| Conformity - CE               |                 |

6819/35-24-500 4/4

| Classifications |  |
|-----------------|--|
| ETIM 9          | EC000133 - Movement sensor/presence detector complete      |
| eClass          | V11.0 : 27144007   |
| WEEE Category   | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B  | Business To Consumer                                       |

| Accessories     |  |                    |          |                    |
|-----------------|--|--------------------|----------|--------------------|
| Identifier      | Description                              | Type 0             | Quantity | Unit Of<br>Measure |
| 2CKA006800A2753 | Presence Detector 12 m studio white matt | 6819/38-24-<br>500 | 1        | piece              |
| 2CKA006800A2765 | Presence Detector studio white matt      | 6889/30-24-<br>500 | 1        | piece              |
| 2CKA006499A0002 | Extension Module                         | 6494-500           | 1        | piece              |
| 2CKA006899A2304 | Protection Cover alpine white            | 6898               | 1        | piece              |

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Wiring\ Accessories\ -\ StandAlone\ Electronics \rightarrow Presence\ Detector \rightarrow Professional\ Series$ 

