



PRODUCT-DETAILS

6819/39-24-500

Presence Detector 12 m DALI studio white matt



Generell informasjon	
Utvidet produkttype	6819/39-24-500
Produkt-ID	2CKA006800A2759
EAN	4011395217832
Katalogbeskrivelse	Presence Detector 12 m DALI studio white matt
Lang beskrivelse	DALI slave presence detector for extension of the detection range of DALI master presence detectors. For the supply of operating voltage via the DALI master. Power consumption on the DALI bus: max. 10 mA, corresponds to approx. 5 DALI operating devices. The communication with the DALI master is carried out via the DALI interface. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Visible height 23 mm. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Surveillance density: 72 sectors with 640 switching segments. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

Installation	
Monteringstype	Built-in
Monteringsposisjon	Ceiling
Mounting Height	Optimum 2 ... 4 m

Environmental	
Omgivelseslufttemperatur	Operation -5 ... +45 °C
Beskyttelsesgrad	IP40

Technical	
Dataark, teknisk informasjon	2CKA001673B9577
Function	Extension unit
Målingsrekkevidde	12 m
Number of Switching Zones	640
Compatible Bus Systems	DALI
Minimum Switching Time	Switch-On 60 second [unit of time]
Connection Type	Plug Clamp
Sensor Type	Passive infrared
Illuminance	5 ... 2000 lx
Sensor Detection Range	360 ° Horizontal 90 ... 360 °

Electrical	
Nominell spenning (U _r)	230 V AC
Auxiliary Voltage AC/DC	9.5 V 22.5 V AC/DC
Inngangsspenningstype	DC
Nominell frekvens (f)	50 / 60 Hz
Power Loss	0.3 W

Design	
Overflatebehandling	Untreated Matt
Material	Thermoplastic
RAL Number	Similar to RAL 9016
Color	studio white matt

Dimensions	
Produktets nettobredde	94 mm
Produktets netto høyde	94 mm
Produktets netto dybde/lengde	72 mm
Produktets nettovekt	140.7 g
Built-In Depth (t ₂)	49 mm

Ordering	
E-Number (Finland)	2619392
E-Number (Sweden)	1301061

Material Compliance		
RoHS-informasjon		2CKA200000E6504
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
REACH Declaration		2CKA309999E9999
REACH Information	True - contains substances > 0.1 mass percentage	
REACH Date		20240705
Conflict Minerals Reporting Template (CMRT)		9AKK108468A3363

Certificates and Declarations		
Samsvarserklæring - CE		2CKA200000E6504

Classifications		
ETIM 9	EC000133 - Movement sensor/presence detector complete	
e-klasse		V11.0 : 27144007
WEEE-kategori	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C/B2B		Business To Consumer

Accessories				
Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006800A2765	Presence Detector studio white matt	6889/30-24-500	1	pièce
2CKA006899A2304	Protection Cover alpine white	6898	1	pièce

Kategorier
Lavspenningsprodukter → Wiring Accessories - StandAlone Electronics → Presence Detector → Professional Series

