

363RAU6W

Panel mounted socket

2CMA167452R1000



Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 63A, IP67 watertight, unified flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Red

GENERAL

| | |
|---------------------|--|
| Product Name | Panel mounted socket |
| Product ID | 2CMA167452R1000 |
| Function | Socket outlet, panel mounting, unified flange, angled |
| EAN | 7392696674522 |
| Catalog Description | Socket-outlet, panel mounting, 6h, 63A, IP67, unified flange, angled, 3P+E |
| Country of Origin | Czech Republic (CZ) |
| E-Number Finland | 2421283 |
| E-Number Norway | 1562073 |
| E-Number Sweden | E2416763 |
| Standards | IEC 60309-1, -2 |
| RoHS Status | Following EU Directive 2011/65/EU |

DIMENSIONS

| | |
|--------------------|----------------|
| Product Net Width | 106 millimetre |
| Product Net Height | 147 millimetre |
| Product Net Length | 147 millimetre |
| Product Net Depth | 147 millimetre |
| Product Net Weight | 0.63 kilogram |

TECHNICAL

| | |
|----------------------|------------------------|
| Product Main Type | TRAU |
| Color | Red |
| Number of Poles | 4 |
| Clock Position | 6Hour |
| Rated Current | 63 ampere |
| Rated Voltage | 380 ... 415 volt |
| Frequency | 50 hertz 60 hertz |
| Degree of Protection | IP67 IP69 |
| Cable Cross-Section | 6...25 mm ² |
| Housing Material | Thermoplastic (PBT) |
| Plug Angle | Angled |
| Product Group | Tough&Safe |

PACKAGING

| | |
|----------------------|----------------|
| Package Width | 112 millimetre |
| Package Height | 139 millimetre |
| Package Gross Weight | 0.63 kilogram |
| Package Length | 112 millimetre |
| Package Units | box 1 piece |