



PRODUCT-DETAILS

# OVR T2 1N 40-275 P TS QS

## OVR T2 1N 40-275 P TS QS Surge Protective Device



General Information	
Extended Product Type	OVR T2 1N 40-275 P TS QS
Product ID	2CTB803972R0500
EAN	3660308519702
Catalog Description	OVR T2 1N 40-275 P TS QS Surge Protective Device
Long Description	Surge protective devices SPD type 2 protect low-voltage consumer systems against surge voltages as they are tested as SPD type 2 according to IEC 61643-11. The devices are compatible with the System pro M compact series. The SPD with "TS" are optionally equipped with a auxiliary contact.

Technical	
Standards	IEC 61643-11 / EN 61643-11
Type of Low Voltage Distribution System	TT TN-S
Suitable For	To protect the systems against the transient overvoltage (lightning)
Rated Voltage (U <sub>r</sub> )	230 V AC
Nominal AC Voltage of the System (U <sub>o</sub> )	230 / 400 V
Voltage Protection Level	1.5 kV

(Up)	(L-N) 1.25 kV (N-PE) 1.4 kV
Maximum Continuous Operating Voltage (U <sub>c</sub> )	(L-PE) 275 V
Temporary Overvoltage Test Value (U <sub>T</sub> )	(L-N) 337 V (N-PE) 1200 V
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	100 kA
Discharge Current	Nominal (8 / 20 μs) 20 kA I (max, 8 / 20 μs) 40 kA
Impulse Current	I (imp, 10 / 350 μs) 2 kA
Short Circuit Withstand I <sub>cc</sub>	100 kA
Power Loss	17 mW
Arrester Class	II
Number of Protected Poles	2
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Poles	2
Number of Conductors	2
Position of Neutral Terminals	Right
Transmission Standard	Optic
Version	Plug-in
Mounting Type	DIN-Rail
Product Type	QS
Options Provided	Residential, commercial building.
Auxiliary Circuit Load	Minimum 12Vdc - 10mA Maximum 250Vac - 1A
Preventive Maintenance Feature	No
Status Indicator	Yes
Fuse Size	2 modular spacing

**Material Compliance**

RoHS Information	9AKK108466A4410
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20220317
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20231212
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

**Environmental**

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000

Dimensions	
Width in Number of Modular Spacings	2
Product Net Width	35.6 mm
Product Net Height	95 mm
Product Net Depth / Length	58 mm
Product Net Weight	0.24 kg

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	250 g
E-Number (Norway)	1672312

Certificates and Declarations	
CB Certificate	2CTC432057G1701
CQC Certificate	9AKK107680A1974
Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4410

Installation	
Instructions and Manuals	2CTC432096M1701

Popular Downloads	
Data Sheet, Technical Information	2CTC432220D0201
Mechanical Drawings	2CTC800021F1200.pdf 2CTC800021F1201.dxf 2CTC800021F1202.stp 2CTC800021F1203.igs

Classifications	
ETIM 8	EC000941 - Surge protection device for power supply systems
ETIM 9	EC000941 - Surge protection device for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363090
eClass	V11.0 : 27130805
Object Classification Code	141DCC

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class II

