

voltage release MX or XF COM - 24..30 V AC/DC

33033

Main

Range	MasterPacT
Range Of Product	MasterPact NT MasterPact NW
Device Short Name	MX com XF com
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Opening coil Closing coil
Control Type	Communicating
[Uc] Control Circuit Voltage	24 V AC 50 Hz 2430 V DC
Circuit Breaker Mounting Mode	Fixed Drawout
Range Compatibility	Masterpact MasterPact NT Masterpact MasterPact NW

Complementary

Operating Threshold	0.71.1 x Un opening
Response Time	55 ms +/- 10 % for MasterPact NT 70 ms +/- 10 % for MasterPact NW 50 ms +/- 10 % for Compact NS630b1600 50 ms +/- 10 % for Compact NS1600b3200
Supply Holding Power	4.5 VA
Accessory / Separate Part Category	Spare part for MasterPact NT Spare part for MasterPact NW

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.1 cm
Package 1 Length	8.6 cm
Package 1 Weight	153.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10

Package 2 Height	9.0 cm
Package 2 Width	18.5 cm
Package 2 Length	13.0 cm
Package 2 Weight	1.61 kg
Unit Type Of Package 3	S03
Number Of Units In Package 3	20
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	4.1 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >

Well-being performance

