



SETRON, cylindrical fuse link, 10 x 38 mm, 20 A, gG, Un AC: 500 V

Figure similar

Model	
product brand name	SETRON
product designation	Cylindrical fuse link
General technical data	
operating class of the fuse link	gG
size of the fuse link	10x38 mm
type of voltage of the operating voltage	AC
operating voltage at AC rated value	500 V
Dissipation	
power loss [W]	2.4 W
power loss [W] for rated value of the current at AC in hot operating state per pole	2 W
Main circuit	
operational current rated value	20 A
Product details	
product component striker	No
Mechanical Design	
mounting position	Any, preferably vertical
net weight	8 g
Approvals Certificates	
General Product Approval	other



[Confirmation](#)



[Confirmation](#)

[Miscellaneous](#)

Environment	
Environmental Confirmations	Environmental Confirmations
Further information	

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NW6007-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NW6007-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW6007-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/13/2023

