

fixed-mounted molded case circuit breaker w. handle frame 1600; 4AUX and trip alarm switch S24; Icu "M" Icu=55kA @ 415V, 4-pole, left ETU360, LSIG, In=1600A rotary coding switch Ir=640...1600A Isd=1...10xIn, li=1.5...15xIn N conductor protec. adjustable OFF, 50%, 100%, 200% gr.-fault prot., can be sw. off Ig=0.1...1 x In, tg=0.1...0.8s nut keeper kit No communication connection, no measurement function Without additional alarm switch assembly With mechanical calling without 2nd auxiliary release without 1st auxiliary release

Model	
product brand name	SENTRON
product designation	Molded case circuit breaker
design of the product	MCCB
product variations	Selective Applications
design of the actuating element	toggel handle actuator
type of the driving mechanism	manual operating mechanism
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU360
General technical data	
number of poles	4
size of the circuit-breaker	1600 A
mechanical service life (operating cycles) / typical	1 000
electrical endurance (operating cycles) / at AC-1 / at 380/415 V	2 000
insulation voltage / rated value	1 000 V
operational current	
• at 45 °C / rated value	1 541 A
continuous current / rated value / maximum	1 600 A
Supply voltage	
operating voltage	
• at AC / at 50/60 Hz / rated value	690 V
Protection class	
protection class IP / on the front	IP20
Breaking Capacity	
switching capacity class of the circuit breaker	M
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	77 W
• maximum	231 W
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	4
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the short-time delayed short-circuit release	
• initial value	1 600 A
• full-scale value	16 000 A
adjustable current response value current / of the current-dependent overload release / initial value	640 A
Product details	
product component	
• trip indicator	Yes
• voltage trigger	No
• undervoltage release	No
product extension / optional / motor drive	No
Product function	
product function	

• grounding protection	Yes
• communication function	No
Display and operation	
display version	Without display
Short circuit	
operating short-circuit current breaking capacity (Ics)	
• at 240 V / rated value	100 kA
• at 415 V / rated value	55 kA
• at 440 V / rated value	55 kA
• at 500 V / rated value	36 kA
• at 690 V / rated value	25 kA
maximum short-circuit current breaking capacity (Icu)	
• at 240 V / rated value	100 kA
• at 415 V / rated value	55 kA
• at 440 V / rated value	55 kA
• at 500 V / rated value	36 kA
• at 690 V / rated value	25 kA
short-circuit current making capacity (Icm)	
• at 240 V / rated value	220 kA
• at 415 V / rated value	121 kA
• at 440 V / rated value	121 kA
• at 500 V / rated value	75.6 kA
• at 690 V / rated value	53 kA
Connections	
arrangement of electrical connectors / for main current circuit	Main connection on front side
type of electrical connection / for main current circuit	busbar connection
Mechanical Design	
height	296 mm
width	280 mm
depth	183 mm
fastening method	fixed mounting
net weight	16 kg
Environmental conditions	
ambient temperature / during operation	
• minimum	-25 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	70 °C
Further information	
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2716-5AD13-0AA0 Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3VA2716-5AD13-0AA0 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2716-5AD13-0AA0 CAX-Online-Generator http://www.siemens.com/cax Tender specifications http://www.siemens.com/specifications	



last modified:

3/16/2020 

