## SIEMENS

## Data sheet

## 3VJ1104-5DB32-0AA0



circuit breaker 3VJ1 IEC framesize 3VJ11 125A line protection ATFM 3-pole Icu=36kA@415V Ics=75% Icu In=40A overload protection Ir=32A...40A shortcircuit protection Ii=600A Screw connection

Model	
product designation	Molded Case Circuit Breaker
design of the product	Line protection
design of the overcurrent release	ATFM
protection function of the overcurrent release	LI
number of poles	3
General technical data	
insulation voltage / rated value	1 000 V
operating voltage / at AC / rated value	415 V
power loss [W] / maximum	31.5 W
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	10.5 W
mechanical service life (operating cycles) / typical	15 000
electrical endurance (operating cycles) / at AC-1 / at 380/415 V	5 000
ground-fault monitoring version	without
Net Weight	1.42 kg
Current	
continuous current / rated value	40 A
operational current	
• at 40 °C	40 A
• at 45 °C	40 A
• at 50 °C	40 A
• at 55 °C	38.88 A
• at 60 °C	37.76 A
Switching capacity according to IEC 60947	
maximum short-circuit current breaking capacity (Icu)	
• at 415 V	36 kA
operating short-circuit current breaking capacity (lcs)	
• at 415 V	27 kA
short-circuit current making capacity (Icm)	
• at 415 V	75.6 kA
Adjustable parameters	
adjustable current response value current / of the current- dependent overload release	32 40 A
adjustable current response value current / of instantaneous short-circuit trip unit	
• minimum	600 A
• maximum	600 A
product function / grounding protection	No
Mechanical Design	
height	150 mm

width	92 mm
depth	85 mm
Connections	
arrangement of electrical connectors / for main current circuit	Front connection
type of electrical connection / for main current circuit	Lug connection line and load side
Accessories	
product extension / optional / motor drive	No
Environmental conditions	
protection class IP / on the front	IP42
ambient temperature	
<ul> <li>during operation / minimum</li> </ul>	-10 °C
<ul> <li>during operation / maximum</li> </ul>	60 °C
during storage / minimum	-15 °C
during storage / maximum	75 °C
Approvals / Certificates	
Test Certificates other	

Type Test Certificates/Test Report

**Confirmation** 

 Further information

 Information on the packaging

 https://support.industry.siemens.com/cs/ww/en/view/109813875

 Information- and Downloadcenter (Catalogs, Brochures,...)

 http://www.siemens.com/lowvoltage/catalogs

 Industry Mall (Online ordering system)

 https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VJ1104-5DB32-0AA0

 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

 https://support.industry.siemens.com/cs/ww/en/ps/3VJ1104-5DB32-0AA0

 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

 https://support.industry.siemens.com/cs/ww/en/ps/3VJ1104-5DB32-0AA0

 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


 http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3VJ1104-5DB32-0AA0

 CAx-Online-Generator

 http://www.siemens.com/cax

 Tender specifications

 http://www.siemens.com/specifications



last modified:

8/9/2023 🖸