

voltage release MN - 200..250 V DC/AC 50/60 Hz

47383

Main

Range	MasterPacT	
Range of product	MasterPact NT MasterPact NW MasterPact NW DC	
Device short name	MN	
Product or component type	Voltage release	
Device application	Control	
Voltage release type	Opening coil Undervoltage release	
control type	Standard	
[Uc] control circuit voltage	200250 V AC 50/60 Hz 200250 V DC	
Circuit breaker mounting mode	Fixed	
Range compatibility	Masterpact MasterPact NT Masterpact MasterPact NW Masterpact MasterPact NW DC	

Complementary

Operating threshold	0.350.7 x Un opening 0.85 Un closing	
Response time	40 ms +/- 5 % for MasterPact NT 90 ms +/- 5 % for MasterPact NW	
Supply holding power	4.5 VA	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.0 cm
Package 1 Length	8.2 cm
Package 1 Weight	172.0 g

Contractual warranty

Warranty 18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	174
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Ad764790-535b-4a4e-825e-50fd804b5824
REACh Regulation	REACh Declaration
China RoHS Regulation	China RoHS declaration
PVC free	Yes

Use Again

○ Repack and remanufacture

Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Product contains halogen above thresholds
Take-back	No