

Product datasheet

Specifications



4 aux.contacts for CB O/C position

47887

Main

Product or component type	Auxiliary contact
Device short name	4 OF
Range compatibility	Masterpact MasterPact NW EasyPact EasyPact MVS EasyPact EasyPact EXE
Signal contacts composition	4 NO/NC

Complementary

Auxiliary contacts type	Standard Low level
Breaking capacity (A)	AC-12: 10 A at 240/380 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-12: 10 A at 480 V AC 50/60 Hz conforming to EN/IEC 60947-2 AC-12: 6 A at 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 DC-12: 10 A at 24/48 V DC conforming to EN/IEC 60947-2 DC-12: 10 A at 125 V DC conforming to EN/IEC 60947-2 DC-12: 3 A at 250 V DC conforming to EN/IEC 60947-2 8 A at 480 V AC 50/60 Hz conforming to UL 489 6 A at 600 V AC 50/60 Hz conforming to UL 489 6 A at 250 V DC conforming to UL 489
Minimum load	100 mA at 24 V 2 mA at 15 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.1 cm
Package 1 Width	4.6 cm
Package 1 Length	6.8 cm
Package 1 Weight	87 g

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
-----------------------	---

RoHS exemption information	Yes
----------------------------	-----

Operations and descriptions

Operation	600
Duration of operation	4 min
Operation Description	Assembly and test

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)