

Product datasheet

Specifications



external power supply module 48/60 V DC

54441

⚠ End-of-service on: 30 June 2022

⚠ Discontinued

Main

Product or component type	External power supply module
Device application	Power supply
Range compatibility	Masterpact (MasterPact NT) circuit breaker Masterpact (MasterPact NW) circuit breaker ComPact (ComPact NS) circuit breaker ComPact (ComPact NSX) circuit breaker ComPact (ComPact NSX DC) circuit breaker PowerPact (PowerPact Multistandard) circuit breaker Masterpact (MasterPact MTZ1) circuit breaker Masterpact (MasterPact MTZ2) circuit breaker Masterpact (MasterPact MTZ3) circuit breaker PowerPact (PowerPact H) circuit breaker PowerPact (PowerPact J) circuit breaker PowerPact (PowerPact L) circuit breaker
Accessory / separate part type	Control units accessories

Complementary

Trip unit name	MicroLogic
[Us] rated supply voltage	48...60 V DC tolerance: +/- 20 %
Output voltage	24 V DC +/-5 %
Overvoltage category	IV conforming to IEC 62477-1
Height	88 mm
Width	105 mm
Depth	59 mm

Environment

Compatibility code	CB_EXTERNAL_POWERSUPPLY
--------------------	-------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.8 cm
Package 1 Width	9.6 cm
Package 1 Length	12.5 cm
Package 1 Weight	346 g

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Recommended replacement(s)