

# PratiKa industrial socket - 125 A - 2P + E - 200...250 V AC - IP67

81190

① Discontinued on: 30 June 2022

• End-of-service on: 28 September 2022

## ① Discontinued

#### Main

Range	PratiKa
Product or component type	Socket
Device short name	PratiKa socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Industrial

### **Complementary**

oompromontary	
Mounting mode	Wall-mounted
Plug, socket, control station shape	Angled
[In] rated current	125 A
[Ue] rated operational voltage	200250 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel
Connections - terminals	Captive screws, completely loosened
Cable cross section	1670 mm²
Cable entry	Cable gland
Thread type	Pg 48
Net weight	1.774 kg
Base dimension	114 x 224 mm
Height	340 mm
Width	114 mm
Depth	213 mm

Colour	Grey (RAL 7035)
Voltage colour	Blue
Environment	
Standards	EN 60309-2 EN 60309-1
IP degree of protection	IP67 conforming to IEC 60529
IK degree of protection	IK08 conforming to EN 62262
Fire resistance	850 °C conforming to IEC 60695-2-11
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient air temperature for operation	35 °C (86400 s)
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.4 cm
Package 1 Width	21.3 cm
Package 1 Length	34 cm
Package 1 Weight	1.808 kg
Offer Sustainability	
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Circularity Profile	No need of specific recycling operations

# Recommended replacement(s)

18 months

**Contractual warranty** 

Warranty