

Product datasheet

Specifications



Isoblock interlocked socket - 32 A - 3P + E - 380...415 V AC - IP65 - wall

82770

Discontinued on: 03 July 2023

Discontinued

Main

Range	PratiKa
Product or component type	Interlocked socket
Device short name	Isoblock socket
Plug, socket category	Low voltage
Industrial socket type	B32/63
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

Complementary

Mounting mode	Wall-mounted
[In] rated current	32 A
[Ue] rated operational voltage	380...415 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Protection type	Without protection
Product compatibility	Modular device
Total number of 18 mm modules	6
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: nickel plated brass
Connections - terminals	Captive screws
Maximum cable cross section	10 mm²
Maximum cable outer diameter	25 mm
Cable entry	Cable gland
Thread type	Pg 21
Net weight	1.7 kg
Base dimension	144 x 371 mm
Height	371 mm

Width	144 mm
Depth	147 mm
Colour	Grey (RAL 7035)
Voltage colour	Red

Environment

Standards	IEC 60309-1 IEC 60309-2
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK10 conforming to EN 62262
Fire resistance	850 °C conforming to IEC 60695-2-11
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient air temperature for operation	35 °C (86400 s) -25...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.6 cm
Package 1 Width	1.5 cm
Package 1 Length	45 cm
Package 1 Weight	1.719 kg
Unit Type of Package 2	P12
Number of Units in Package 2	32
Package 2 Height	150 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	67.008 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)