

# Product datasheet

Specifications



## Isoblock interlocked socket - 63 A - 3P + E - 380...415 V AC - IP65 - wall

82782

### Main

Range	Mureva
Product or component type	Interlocked socket
Device short name	Isoblock socket
Plug, socket category	Low voltage
Industrial socket type	B32/63
Poles description	3P + E
Network type	AC
Outlet standard	Industrial

### Complementary

Mounting mode	Wall-mounted
[In] rated current	63 A
[Ue] rated operational voltage	380...415 V
Network frequency	50/60 Hz
Ground lug clockwise position	6 h
Protection type	Without protection
Product compatibility	Modular device
Total number of 18 mm modules	6
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Sleeves: nickel plated brass
Connections - terminals	Captive screws
Maximum cable cross section	35 mm²
Maximum cable outer diameter	25 mm
Cable entry	Cable gland
Thread type	Pg 29
Net weight	2.3 kg
Base dimension	144 x 389 mm
Height	389 mm
Width	144 mm

Depth	147 mm
Colour	Grey (RAL 7035)
Voltage colour	Red

### Environment

Standards	IEC 60309-2 IEC 60309-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK10 conforming to EN 62262
Fire resistance	850 °C conforming to IEC 60695-2-11
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient air temperature for operation	35 °C ( 86400 s ) -25...40 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.500 cm
Package 1 Width	15.000 cm
Package 1 Length	41.000 cm
Package 1 Weight	2.288 kg
Unit Type of Package 2	P12
Number of Units in Package 2	12
Package 2 Height	45.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	27.456 kg

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Circularity Profile	No need of specific recycling operations

### Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)