



### Main

Range of product	9007
Series name	Heavy duty
Head type	Rotary head
Type of operator	spring return lever arm (standard pre-travel) (to be ordered separately)
Switch actuation	CW
Cable entry	NPT conduit entry, cable outer diameter: 12.7 mm
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action

### Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	0.5 N.m
[Ie] rated operational current	10 A, A600 10 A, Q600
[Ui] rated insulation voltage	600 V
Local signalling	without
Product certifications	CE[RETURN]UL listed[RETURN]CSA
Provided equipment	Receptacle

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.318 cm
Package 1 Width	7.112 cm
Package 1 Length	10.922 cm
Package 1 Weight	600.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	12.446 cm
Package 2 Width	14.732 cm
Package 2 Length	22.86 cm
Package 2 Weight	5.729 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>