



Main

Range of product	9007
Series name	Heavy duty
Device short name	C
Head type	Turret head rotary lever
Type of operator	Spring return lever arm (standard pre-travel) (to be ordered separately drive shaft (reduced diameter to 0.306 in)lever arm
Switch actuation	CW
Cable entry	NPT conduit entry, cable outer diameter: 12.70 mm
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action

Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	0.5 N.m
Tripping angle	4 °
Maximum displacement angle	90 °
[Ie] rated operational current	10 A, A600 10 A, Q600
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	600 V
Local signalling	without pilot light
Product certifications	UL listed[RETURN]CSA[RETURN]CE
Provided equipment	Receptacle


Environment

Ambient air temperature for operation	-29...85 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.064 cm
Package 1 Width	6.858 cm
Package 1 Length	10.668 cm
Package 1 Weight	566.991 g

Offer Sustainability

Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com