

## Main

Range of Product	9007
Series name	Severe duty
Product or Component Type	Limit switch lever
Device short name	9007T/FT
Associated head	9007CS9 9007T5S9 9007NS9 9007AS9 9007T10S9 9007BS9
Associated complete product	9007FT 9007C...S9 9007T
Movement of operating head	Rotary
Type of operator	Cast zinc spring return rod lever without rod - clamp for use with 1/4" key stock (not supplied)
Type of approach	Lateral approach
Positive opening	Without

## Complementary

Switch actuation	By any moving part
Net Weight	0.1 lb(US) (0.05 kg)

## Environment

Ambient Air Temperature for Operation	-23.3...85.0 °C (-10...185 °F)
Ambient Air Temperature for Storage	-23.3...85.0 °C (-10...185 °F)
Environmental characteristic	Standard environment

## Ordering and shipping details

Category	US10DS121494
Discount Schedule	0DS1
GTIN	785901814122
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.200 in (3.048 cm)
Package 1 Width	1.400 in (3.556 cm)
Package 1 Length	2.0000000000 in (5.08 cm)
Package 1 Weight	2.72 oz (77.11 g)
Unit Type of Package 2	S01
Number of Units in Package 2	50
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	5.9 in (15.0 cm)

Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	9.070 lb(US) (4.114 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>

### Contractual warranty

Warranty	18 months
----------	-----------