# **Product datasheet**

Specifications





# extension ETL iTL 32 - 1P -1NO - 32A - coil 110 VDC - 230...240VAC 50/60Hz

A9C32836

#### Main

Range Of Product	Acti9	
Product Or Component Type	Extension for impulse relay	
Device Short Name	iETL iTL 32	
Relay Application	Remote control	
Poles Description	1P	
Pole Contact Composition	1 NO	
[In] Rated Current	32 A	
Network Type	AC	

#### Complementary

Complemental y		
Network Frequency	50/60 Hz	
[Ue] Rated Operational Voltage	415 V AC 50/60 Hz	
Control Type	Toggle Remote control	
Control Signal Type	Impulse	
Switching Frequency	5 switching operations/minute	
Impulse Duration	50 ms	
Remote Control Type	Illuminated push-button 3 mA	
Local Signalling	ON/OFF indication	
[Uc] Control Circuit Voltage	230240 V AC 50/60 Hz 110 V DC	
Supply Inrush Power	19 VA	
Mounting Mode	Fixed, on right side of TL	
Mounting Support	35 mm symmetrical DIN rail	
9 Mm Pitches	2	
Height	60 mm	
Width	18 mm	
Depth	84 mm	
Colour	White	
Electrical Durability	AC-21: 50000 cycles AC-22: 20000 cycles	
Connections - Terminals	Tunnel type terminals - <= 10 mm²	
Range Compatibility	Acti 9 Acti9 iTL iTL	

Product Compatibility ITL 32A

#### **Environment**

Standards	EN 669-1 EN 669-2-2	
Noise Level	60 dB	
Ip Degree Of Protection	IP20 conforming to IEC 60529	
Pollution Degree	3	
Tropicalisation	2 conforming to IEC 60068-1	
Relative Humidity	95 % at 55 °C	
Ambient Air Temperature For Operation	-2050 °C	
Ambient Air Temperature For Storage	-4070 °C	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.2 cm
Package 1 Width	8.4 cm
Package 1 Length	9.4 cm
Package 1 Weight	120 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	8
Package 2 Height	9 cm
Package 2 Width	10 cm
Package 2 Length	26.5 cm
Package 2 Weight	1.021 kg
Unit Type Of Package 3	\$03
Number Of Units In Package 3	72
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	9.683 kg

### **Contractual warranty**

Warranty 12 months



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>Ø</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes
<b>⊘</b>	Halogen Free Plastic Parts Product	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations